



ALCOLIN WALLPAPER PASTE



Description

ALCOLIN WALLPAPER PASTE is a cellulose-based powder that mixes easily with water to form a soft gel-like paste used for hanging up standard wallpaper

Features & Benefits

- Water soluble - easy to mix
- Enhanced slip - easy to slide wallpaper into position and to reposition
- Extended open time – sufficient working time
- Non-toxic – safe to use

Application

- ALCOLIN WALLPAPER PASTE is suitable for hanging light and medium weight wallpapers
- By mixing with ALCOLIN PERMOBOND, it can be used for heavy weight paper i.e. vinyl paper, textile coverings, etc
- Ideal for putting up public posters and adverts on cardboard
- Ideal for wallpaper borders (narrow strips of wallpaper used to decorate a wall)
- Suitable for paper mache
- When mixed with food dye, it can be used as a safe finger paint

Adhesion

ALCOLIN WALLPAPER PASTE bonds light and medium duty wallpaper to a variety of surfaces, including

- water based acrylic paints
- primed oil, alkyd and enamel painted surfaces
- primed absorbent surfaces like cardboard and plaster

Limitations

- Not suitable for direct application over oil/alkyd/enamel painted surfaces
- Do not apply wallpaper onto damp walls as this encourages mould growth and decreases adhesion of the paper

Safety instructions

Although ALCOLIN WALLPAPER PASTE is non-toxic, safe handling practices should still be implemented to avoid irritating sensitive skin. Wear rubber gloves to avoid direct contact with skin. In the event of skin or eye contact, rinse thoroughly with cold water. Seek medical assistance if irritation or discomfort persists

Refer to our Material Safety Data Sheets for further toxicological information and comprehensive handling instructions

Surface preparation

The surface coming into direct contact with ALCOLIN WALLPAPER PASTE must be clean, dry and free from all loose materials i.e. dust, dirt, flaking paint, old wallpaper and any other contaminants. Mouldy areas should be treated with a bleach solution

Remove any switch plates and wall fixtures. Fill any cracks and holes with a suitable crackfiller such as ALCOLIN FLEXIFILL, ALCOLIN LITEFILL, ALCOLIN EXTERIOR CRACKFILLER, ALCOLIN INTERIOR CRACKFILLER or ALCOLIN ACRYLIC SEALANT

For best results clean surface with



ALCOLIN SUGAR SOAP

TECHNICAL DATA SHEET

Oil, alkyd and enamel painted surfaces: prime with diluted ALCOLIN PERMOBOND

Porous surfaces: must be primed with a coating of the ALCOLIN WALLPAPER PASTE. Allow to dry before applying the paste to the paper

Poor surface preparation may result in adhesion failure

Directions for use

- Ensure that surfaces are prepared as above
- Ensure that the room is well ventilated
- Add 50g ALCOLIN WALLPAPER PASTE into 2 to 3 litres of preferably warm water and stir for approximately 4 minutes until a paste is formed
- For heavy duty application add 500ml of ALCOLIN PERMOBOND to the paste and stir until smooth
- Starting at the middle of the paper brush or roller the mixed ALCOLIN WALLPAPER PASTE evenly and not too thickly making sure to cover all the edges
- To hang the wallpaper, follow the standard wallpaper hanging procedures
- Starting from the top, place the paper in place taking care to roll out air bubbles and uneven patches of paste
- Ensure that the front surface of the paper is kept free from paste. Remove any splashes or excess paste with a damp cloth
- The mixed paste should be refrigerated to extend mixed pot life

Cleaning

Clean tools with water

Storage stability

ALCOLIN WALLPAPER PASTE has a shelf life of at least 18 months if stored in a cool (below 25°C), dry place in a sealed bag. If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable. Made up paste should be used within one week, provided that it is kept refrigerated

Product packaging

50g unit

Product data

i. Physical data

Appearance	Cream coloured powder
Solids	100%
Consistency - when mixed with water	Soft gel

ii. Application data

Mixing ratio - standard wallpaper	50g into 2 to 3 litres of warm water
Heavy duty application	50g into 2 to 3 litres of warm water + 500g Alcolin Permabond
Pot life	1 week
Setting time	24 hours
Coverage	Approx. 20m ² per 50g unit

The above information is only offered, as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for problems caused by the use and/or application of this product.

Head Office: +27(0) 21 555 7400
Toll-Free No: 0800 222 400
Beverley Close, Montague Gardens, 7441



TECHNICAL DATA SHEET

PO Box 37008, Chempet, 7442
www.alcolin.com

