

PREMIUM INTERIOR/EXTERIOR HIGH GLOSS PAINT

SUPERGLOSS ENAMEL



CODE:

DSG

Description:

A high quality alkyd based high gloss enamel.

Product Benefits:

Dries to a tough durable finish with a very good weather resistance. Use as a decorative and protective coating for all exterior and interior surfaces. Excellent obliteration properties.

SURFACE PREPARATION:

New Work:

1. Concrete and plaster surfaces must be primed with Alkali Resistant Primer.
2. Wooden surfaces must be primed with Wood Primer and Universal undercoat.
3. Metal surfaces must be primed with RP4, excluding very smooth surfaces e.g. New Mild steel, galvanising or aluminium which must be coated with Vinyl Wash Primer / Acid Etch Primer and Universal Undercoat.

Previously Painted Surfaces:

1. Surfaces must be in sound condition.
2. Loose and flaking paint must be removed.
3. Old enamel or oil paints must be sanded and suitably primed.
4. Chalky surfaces must be well brushed and sealed with Alkali Resistant Primer.

General:

1. All substrates should be clean, dry, sound and free of grease and oils before painting.
2. Hairline cracks, imperfections should be filled with a suitable Masonry Crack Filler, and primed with Masonry Primer, before application of the paint system.
3. Consult our sales staff for application onto any other substrate.
4. Not compatible with pliolite based products e.g. Masonry Primer.

APPLICATION:

Ready to use. Brush or roller application.
Apply 2 coats sanding lightly between coats.

TECHNICAL DATA:

SG:	+/- 1.00
Viscosity:	60 - 70 KU
Drying Time (T):	4 hours
@ 25°C (H):	16 hours
Over coating:	16 hours
Solid Mass:	+/- 50 %
Finish:	High Gloss
Spread Rate:	8 - 10m ² /Lt depending on surface substrate
Colour Range:	White & colours as per colour card
Bases:	Pastel, Deep, Transparent.
Gloss @ 60°:	> 75%

Note: Certain transparent colours may require a minimum of 3 coats to achieve total obliteration.