



Hall's
MANUFACTURING

Pink Wood Primer

Technical Data Sheet

Description:

Pink Wood Primer is an oil-based wood primer, which is primarily used to protect all exterior timber surfaces. This product has excellent filling and sealing properties and is normally used in conjunction with a universal undercoat, and the appropriate finish coat/s of paint.

Surface Preparation:

Ensure surface is dry and in sound condition, free from dust, grease, oil, algae, fungus or any loose particles.

Product Application:

Stir the contents thoroughly before use

This product should be applied without thinning. If thinning is required use Mineral Turpentine

Apply this product with a Brush or Mohair Roller

Allow overnight drying time before applying the final coat/s of paint

Clean tools with Mineral Turpentine

Wooden surfaces such as garden sheds; dog kennels & pergolas that are to be painted

Good adhesion properties

Excellent hiding power

Caution:

Applying coats too thick can cause wrinkling and running.

Very cold conditions will extend drying times. Do not apply coatings when outside temperatures are 4 degrees and below.

Use	:	Interior & Exterior
Appearance	:	Matt Finish
Drying Time	:	16 hours
Recoat Time	:	16 hours
Spread Rate	:	8 – 10sq m/ Litre
Cleaning	:	Mineral Turpentine
Thinning	:	Not recommended

Safety:

Keep out of reach of children.

Avoid swallowing. If swallowed, induce vomiting, and seek medical attention immediately.

Avoid eye contact. In case of eye contact, rinse eyes thoroughly with water, seek medical attention immediately.