



## **FENCE DEFENCE**

### **DESCRIPTION:**

*Powafix Fence Defence is a water based Carbolineum alternative that is formulated to waterproof and protect treated timbers. The low odour characteristics mean that Fence Defence can be used in both interior and exterior applications. Fence Defence seals in the chemicals that protect pre-treated timber from termite and wood borer whilst also preventing wood rot and decay.*

### **RECOMMENDED USES:**

- Roof trusses, battens and fascia's.
- Fences, gates and poles.
- Garden huts, log cabins, dog kennels and jungle gyms and animal enclosures.

### **FEATURES & BENEFITS:**

- Water based creosote alternative used to waterproof & protect treated timber.
- Protects timber against rot & decay.
- Low odour.
- Interior/Exterior

### **PRODUCT INFORMATION:**

- Shake well before use.
- Do not apply to freshly cut timber or timber that is excessively wet.
- Stains timber a dark brown / black colour.
- Fence defence can only be applied to timber that has been pre-treated against insect attack as it does not contain any insecticide preservative.

### **STORAGE INSTRUCTIONS:**

- Ensure cap is tightly sealed and product is kept upright at all times.
- Secure product when transporting to prevent accidental spillage.
- Dispose of empty container and do not use for any other purpose.
- Do not dispose product into common waste system.
- Contact 086 025 4620 for product disposal enquiries.

### **SURFACE PREPRATION:**

- Remove excess, loose or flaking material with a wire brush or medium grit sand paper.
- Clean timber with Powafix Liquid Sugar Soap to remove any grease, oil or dirt

### **DIRECTIONS FOR USE:**

- ONLY apply Fence Defence to pre-treated timber- H4 or higher.
- Apply liberally with block brush or coarse bristle brush. Work product into all cracks, holes and blemishes to ensure the timber is sealed.
- New timber not previously treated with Fence Defence should be treated with 2 coats.
- If Fence Defence is to be used with timber below ground (anchor posts) treat base of the poles with 3 coats.
- Allow 2 – 4 hours drying time between coats.
- A maintenance coat should be applied every 12 – 18 months for exterior timber.



### SAFETY INSTRUCTIONS

READ INSTRUCTIONS BEFORE USE



Toxic to aquatic life with long lasting effects



**WARNING**

May cause an skin allergic reaction



Use protective glasses. If contact with eyes occurs, flush open eyes with plenty of water and seek immediate medical attention.



Wear protective gloves. Avoid contact with skin. If contact with skin occurs, wash with soapy water.






Store in a secure location, out of reach of children and animals. If swallowed do not induce vomiting and seek immediate medical attention.

**Poison Info. Line: 021 689 5227 / 0861 555 777**



**GALLERY:**

		
1L Polycan 8 per case FEND1L BLACK 6009600996366	1L Polycan 8 per case FEND1LBR BROWN 6009600996540	1L Polycan 8 per case FEND1LGR GREEN 6009600996571

		
5L Polycan 4 per case FEND5LGR GREEN 6009600996588	5L Polycan 4 per case FEND5LBR BROWN 6009600996557	5L Polycan 4 per case FEND5L BLACK 6009600996199

\*25L image available on request.

**COLOUR:**

- Black
- Green
- Brown

**ASSOCIATED PRODUCTS:**

- Powafix Sugar Soap
- Powafix Lacquer Thinners
- Powafix Eco Powa Brush Cleaner



More than just a product.

# TIMBER TREATMENT PRODUCTS TECHNICAL DATA SHEET



## **SPECIFIC DATA:**

APPEARANCE:	LIQUID.
DENSITY:	1.18 – 1.27 KG/ L
ODOUR:	MILD
FLAMMABILITY:	NON FLAMMABLE
OPEN TIME:	N/A
PH:	8.5 – 9.5
FLASH POINT:	N/A

CODE & ISSUE DATE:  
FEND JAN 2017

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.