



Amended FEB 2022

## DATA SHEET- ACRYLIC MATT SEALER

### DESCRIPTION:

Africote Acrylic Matt Wall Sealer is a pure acrylic based Wall Sealer containing a syloid matting agent that gives a low sheen matt finish.

### USES:

Sealing of Africote stucco and Roman wall plaster's in lounges, bedrooms etc not to be used as a final sealer in areas that have moisture ie: bathrooms. Do not use as a final floor sealer, contact Africote technical services to discuss the correct floor sealers. Sealing of Rust and Copper paint.

### Additional uses:

Used as a primer on raw concrete prior to a cementitious application this assists with pin holing. Matt sealer is used as a colour retainer to prevent concrete finishes from going darker.

**NB:** Not suitable for use in showers or moist areas, where hot water and steam is present. Will discolour or whiten in these areas.

### SURFACE PREPARATION AND INSPECTION:

Make sure all surfaces are dust free. As a precaution wipe down all surfaces with a damp mutton cloth before applying Africote Matt Sealer.

All surfaces must be dry before application.

Do not apply to hot, sun-baked surfaces. The coating can end up too thick with unsightly brush or roller marks.

### METHOD OF APPLICATION:

Use a soft brush or apply with a tile sponge.

**CAUTION:** Matt sealer must be applied and brushed or rolled completely. Any run marks will cause white deposits and streaks that are unsightly.  
Stir contents of drum continuously to make sure that the matting agent does not settle.  
Allow at least 6 hours between coats – 2 coats recommended

**COVERAGE:** 12 to 15 square meter per litre per coat.

**PACKAGING:** 1, 5 and 20 litre branded plastic buckets.

**SHELF LIFE:** 6 Months

**CLEANING OF TOOLS:** Clean tap water

### HEALTH AND SAFETY:

This product contains solvent. Avoid inhalation. Contact with wet product may cause irritation or burns to sensitive skin. Wear suitable protective clothing, gloves and eye/face protection. In case of insufficient ventilation, wear suitable respiratory protection (cartridge type respiratory mask).

**FIRST AID:**

**Eyes:** In case of contact with eyes do not rub. Immediately flush with plenty of water.  
**Skin:** Wash thoroughly with soap and water. Remove soiled clothing.  
**Inhalation:** Move to fresh air.  
If symptoms persist or develop, or if ingested, seek medical attention. Wash thoroughly immediately after handling.

**DO NOT TAKE INTERNALLY – KEEP OUT OF REACH OF CHILDREN-THIS PRODUCT IS NOT FLAMMABLE**

NB: **No** claims will be entertained where applications are done using other manufacturers products in combination with Africote products. This includes bonding liquids, filler coats, sealers, undercoats etc.

**NB:** Due to ongoing research and development undertaken on our coatings and the application process, coupled with technological advances in the industry, please consult our factory to ensure you have the latest Data Sheet.

Unit 22 Sun View Centre, 7 North Reef road, Bedfordview East Germiston, P.O Box 357 Bedfordview, 2008,  
South Africa

Directors: V.P. Ghisleni, H.B. De Abreu, R.P Ghisleni  
VIST OUR WEBSITE AT: [www.africote.co.za](http://www.africote.co.za)