

Woodoc 5 Specification Sheet



Typical Application:

Apply Woodoc 5 to hardwood tables, chairs, other furniture and interior woodwork where the beauty of a natural "oiled" look is required. Only for interior use. **Not suitable for use on floors.**

Product Features:

Woodoc 5 creates an absolute matt or natural looking surface that is nevertheless totally stain-, water-, alcohol- and heat-resistant.

- Easy to apply.
- Penetrates wood, binds with it and lends a flexible yet strong and resistant surface finish.
- Suitable for all types of wood.
- Non-toxic once dry.
- Complete how-to-use instructions on label.

No: WD5/006

Dated: 03/10/19

Name:

Woodoc 5 - Interior Matt Polywax Sealer

Description:

A natural "oiled" finish.

Coverage:

First coat 10-12 m²/litre. Subsequent coats 12-14 m²/litre. 3 coats (average) 3,3 m²/litre.

Application:

Paint brush. Clean brush with mineral turpentine.

Dilution:

Not recommended.

Drying Time:

Drying will vary, depending on moisture and atmospheric conditions.

Product Properties:

Clear, lead-free, indoor wood sealer

Formaldehyde-Free.

Wax Content:

High

Compatibility:

Mineral Turpentine.

Non-Compatibility:

Acetone, Lacquer Thinners, Benzene and other solvents.

Packaging:

500 ml, 1 litre and 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE TIN BEFORE STARTING WORK.

FLAMMABLE. Keep out of reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.

IMPORTANT: This product hardens through contact with air (oxygen). Replace lid firmly after use to prolong pot life.



Manufactured and marketed by:

Rekara Mills (Pty) Ltd

PO Box 16, Fort Beaufort 5720, South Africa

Tel +2746 645 1109 Fax +2746 645 1538

Customer Service:

Toll-Free during office hours 0800 411 200 (South Africa only)

Email: information@woodoc.com or visit www.woodoc.com