Woodoc Penetrating Weatherproof Wax Specification Sheet



Typical Application:

A liquid penetrating weatherproof wax with ultra-violet filters for sealed/treated exterior wood. The product treats wood effectively in spite of the presence of waxes, oils, varnishes or sealers. Wood should first be sealed with a Woodoc Exterior Sealer. Note: If the product is used on wooden decks or – staircases, apply very sparingly as the surface can become slippery.

Product Features:

Woodoc Penetrating Weatherproof Wax penetrates the existing sealer or coating to feed the wood. The wax content helps exclude moisture, whilst the UV-absorber replenishes the sealer's UV-resistance.

- Enhances the protection of wood against seasonal and environmental changes.
- Brings out the natural colour and grain of wood.
- Revitalises the surface coating, cleaning and refreshes it.
- Non-toxic when dry.
- Compatible with most varnishes, sealers and finishes.
- Unlimited shelf life.
- Complete how-to-use instructions on label.

No: WDpwwax/003 **Dated:** 03/08/15

Name:

Woodoc Penetrating Weatherproof Wax

Description:

Exterior maintenance and refurbishing wax.

Coverage:

Dependant on application.

Application:

By brush or cloth.

Drying Time:

Not Applicable.

Product Properties:

A clear liquid wax formulated for maximum penetration.

Wax solidifies and precipitates at low temperatures.

Density @ 20° C: 0,75 (water = 1)

Lead-Free. No hazardous decomposition materials.

Flammable.

Wax Content:

High

Should not be thinned.

Packaging:

375 ml, 1 litre, 5 litres. (20 or 200 litres available on request from dealer)

ALWAYS READ THE DIRECTIONS ON THE CONTAINER BEFORE STARTING WORK. Shake before use.

FLAMMABLE. Keep out of the reach of children. Harmful when consumed. Ingestion may cause chemical pneumonitis.



Manufactured and marketed by: Rekara Mills (Pty) Ltd PO Box 16, Fort Beaufort 5720, South Africa Tel +2746 645 1109 Fax +2746 645 1538