



ACRYLIC PVA WALL & CEILING PAINT

PRODUCT DESCRIPTION:

Powafix Acrylic PVA is brilliant white, smooth matt wall and ceiling paint, offering a high hiding finish that obliterates plaster imperfections and blemishes. Powafix Acrylic PVA is formulated for easy application and can be used for interior and exterior surfaces. This high quality product is backed by a 5 year guarantee

FEATURES:

- Interior
- Exterior
- Smooth Matt Finish
- Easy to apply

SURFACE PREPARATION:

- Remove all loose and flaking material.
- Ensure surface is sound and free of any dust, dirt, grease and oil contaminants.
- Clean all surfaces with the appropriate Powafix cleaner.
- Never apply Powafix Acrylic PVA over any material that may adversely affect the adhesion of the paint.

SURFACE	POWAFIX PREPARTION	POWAFIX PRIMER
Cement Plaster, Concrete and Fibre Cement	Clean all surfaces with Powafix Sugar Soap* and remove all algae and fungus with Powafix Fungi Fix*.	Prime with Powafix Plaster Primer*
Metal and Galvanised Steel	Metal and rusted surfaces must be cleaned with Powafix Deoxidene* and rinsed thoroughly with water.	Prime with 2 coats of Powafix Metal Primer*
Wooden Facias, Barge Boards and Trusses	Ensure surface is clean and in sound condition. Timber must be free of wood rot, moisture, borer and termites. Sand smooth before applying paint.	Prime with Powafix Pink Wood Primer* or Powafix Universal Undercoat*

POWAFIX APPROVED PRODUCTS:

- All cracks, holes and imperfections are to be filled with an appropriate Powafix filler / skimmer and spot primed to achieve a consistent sheen level. Powafix manufactures Fill 'n Fix* and repairs all cracks and holes. This ready to use product is highly effective at repairing surfaces prior to painting. Powafix manufactures Powaskim Highbuild* and Superfine* skimming products to achieve a uniform smooth finish when plaster work is not even.

STORAGE PRECAUTIONS:

- Ensure lid is tightly sealed and product is kept upright at all times.
- Secure product when transporting to prevent accidental spillage.
- Do not dispose product into common waste system.
- Dispose of empty container and do not use for any other purpose.
- Contact 0860 254 620 for product disposal enquiries.
- Discard of product 18 months after batch date.



GUARANTEE INFORMATION:

1. Terms and Conditions apply.
2. Project must be registered with Powafix before any surface preparation and coating application commences.
3. Terms and conditions are available on request.
4. This product is only guaranteed when used on an interior surface.

* Use product directions displayed on respective products.

APPLICATION PRECAUTIONS:

- Ensure the surfaces have been thoroughly cleaned and treated.
- All cracks, holes and imperfections to be filled with an appropriate Powafix filler / skimmer and spot primed to achieve a consistent sheen level.
- Chalky substrates are to be primed with an appropriate solvent based bonding liquid and left to dry for 16 hours before over coating.
- Only paint on a dry surface. Moisture content must not exceed 15%.
- Do not paint in cold weather below 8°C or if imminent rainfall is expected.
- Drying times will be extended during cold weather conditions.
- Check batch numbers are the same to ensure colour consistency.
- Allow 2 – 3 hours drying time between coats.
- Always apply a minimum of two coats to achieve a total dry film thickness of 70 - 80 microns (35-40 microns per coat).
- Coverage of Powafix Acrylic PVA will depend on porosity of the surface that it is being applied to.
- Store in cool, dry area.
- Clean all equipment with warm water and Powafix Sugar Soap*.

SAFETY INSTRUCTIONS READ INSTRUCTIONS BEFORE USE	
	Use protective glasses. If contact with eyes occurs, flush open eyes with plenty of water and seek immediate medical attention.
	WARNING! Causes mild skin irritation. Wear protective gloves. Avoid contact with skin. If contact with skin occurs, wash with soapy water. Do not eat, drink or smoke when using product. Take off contaminated clothing and wash before re-use.
	Store out of reach of children and animals. If swallowed do not induce vomiting and seek immediate medical attention.
Poison Info. Line: 021 689 5227 / 0861 555 777	



GALLERY:

	
5L Can 4 per case CLIMACRPVA5LT 6009600996649	20L Can 1 unit CLIMACRPVA20LT 6009600996656

COLOUR:

- Dries white after mixing.

ASSOCIATED PRODUCTS:

- Powafix Fill 'n Fix
- Powafix Powaskim Superfine
- Powafix Powaskim Highbuild
- Powafix Sugar Soap
- Powafix Fungi Fix
- Powafix Plaster Primer
- Powafix Metal Primer
- Powafix Pink Wood Primer
- Powafix Universal Undercoat
- Powafix Deoxidene



More than just a product.

PAINTS & ENAMELS TECHNICAL DATA SHEET



SPECIFIC DATA: INCOMPLETE

SPREADING RATE:	8 – 10m ²
RECOATING TIME:	4 HOURS
DRYING TIME:	6 HOURS
CLEAN UP:	WATER
THINNER:	WATER
APPLICATION TEMPERATURE:	8°C - 35°C
SG:	1.35 – 1.40
PH:	8.0 – 9.5
SHELF LIFE:	MINIMUM 12 MONTHS WHEN STORED TO MANUFACTURERS RECOMMENDATIONS.

CODE & ISSUE DATE:

CLIMACRPVA JAN 2017

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.