



FILL 'N FIX

DESCRIPTION:

Powafix Fill 'n Fix is a highly flexible, ready to use interior and exterior Crack Filler paste with excellent adhesion properties.

RECOMMENDED USES:

- Repairs cracks, holes and blemishes in bricks, concrete, plaster, stone and other masonry surfaces.
- The excellent adhesion properties makes it suitable for use on timber, ceiling and cement fibre boards.
- Fill 'n Fix is compatible with both water based and solvent based paints and requires no primers when painting.

FEATURES & BENEFITS:

- Excellent adhesion.
- Ready to use.
- Interior / exterior.
- Highly flexible.

TOOLS:

- 75mm scraper.
- Bucket for clean water.
- Powafix Builder's Sponge*.
- Medium to fine grit sand paper.

TOP TIPS:

- Wiping the surface to be repaired with a damp sponge before skimming will make it easier to apply Powafix Fill 'n Fix and will improve the adhesion.

DIRECTIONS FOR USE:

- The surface must be completely clear of loose or flaking material.
- Clean all surfaces with Powafix Sugar Soap* prior to applying Powafix Fill 'n Fix.
- Wipe the surface to be repaired with a damp sponge, to make it easier to apply Fill 'n Fix.
- Plaster or concrete surfaces must be primed with an alkali resistant plaster primer before using Fill 'n Fix.
- Apply product with putty knife or scraper by pressing the product firmly into the cavity. Use a wet putty knife to smooth the product down.
- A damp sponge can also be used to smooth off Fill 'n Fix 15 – 30 minutes after application.
- Do not allow Fill 'n Fix to dry for more than 2 – 3 hours or overnight because Fill 'n Fix's weather resistant formulation dries very hard and becomes more difficult to sand the longer it is left to dry.
- Deep cracks must be filled in 3 – 5 mm layers to ensure thorough drying.
- No primer needed, Fill 'n Fix can be overcoated with either a water or solvent based coating 3 – 4 hours after applying.

*Water based paint coating can be over coated within 3 – 4 hours.

*Solvent based paint coating should only be used after 24 – 36 hours to make sure the Fill 'n Fix has had enough time to cure.



USAGE AND STORAGE PRECAUTIONS:

- Ensure lid is tightly sealed and packaging is secure and upright at all times.
- Put a small amount of water on top of the product to prevent it from drying out before placing the lid onto the container.
- Store product in cool, well-ventilated area.
- Secure product when transporting to prevent accidental spillage.
- Dispose of empty container and do not use for any other purpose.
- Do not dispose product into common waste system.
- Contact 0860 254 620 for product disposal enquiries.

*Use product directions displayed on respective products.

SAFETY INSTRUCTIONS READ INSTRUCTIONS BEFORE USE	
	Use protective glasses. If contact with eyes occurs, flush open eyes with plenty of water and seek immediate medical attention.
	Wear protective gloves. Avoid contact with skin. If contact with skin occurs, wash with soapy water. Do not eat, drink or smoke when using product. Take off contaminated clothing and wash before re-use.
	Store in a secure location, out of reach of children and animals. If swallowed do not induce vomiting and seek immediate medical attention.
Poison Info. Line: 021 689 5227 / 0861 555 777	



GALLERY:

			
500ML Tub 6 per carton CFR500MLS 6009600990135	1L Tub 8 per carton CFR1LS 6009600990142	2.5L Bucket Each CFR2.5LS 6009600992825	5L Bucket Each CFR5LS 6009600990722

COLOURS:

- Dries white.

ASSOCIATED PRODUCTS:

- Universal Undercoat.
- Powafix Sugar Soap.
- Plaster Primer.

SPECIFIC DATA:

APPEARANCE:	CREAMY WHITE PASTE.
SG@23°C:	1.96
APPLICATION TEMP:	8°C → 35°C
OPEN TIME:	N/A
MAXIMUM APPLICATION: THICKNESS:	3 – 5mm
SHELF LIFE:	MINIMUM 12 MONTHS WHEN STORED TO MANUFACTURERS RECOMMENDATIONS.

CODE & ISSUE DATE:
CFF JAN 2017

The information contained on this Technical Data Sheet is, to the best of our knowledge, true and accurate. As the conditions of use are not under our control, no warranty is given or implied in respect of such information, or in respect of any recommendations or suggestions which may be made.