



DIY Waterproofing and Damp-proofing solutions.

SLURRYSEAL

Cementitious Waterproofing Kit

Description

A two component, cementitious, waterproofing slurry ideal for shower cubicles, balconies, ponds, foundation and retaining walls, for both positive and negative applications

Discussion

A two component, flexible, cementitious, waterproofing slurry. Ideal for use in both negative and positive applications as well as permanent submerged applications. Uses include; shower cubicles, retaining walls, foundations walls, flowerboxes, fish ponds, as well as under tile applications such as small balconies and patios. Slurry Seal can be used in conjunction with a POLYPROPYLENE reinforcing membrane in areas exposed to movement or cracking.

Application

1. As with any painting/coating process correct surface preparation is essential. All areas being treated must be thoroughly cleaned removing all loose material, dust, dirt, grime, or any other barrier to adhesion.
2. Using clean water dampen all surfaces just prior to application of the Slurry Seal.
3. Using the bucket provided first pour in component A (White milky liquid). While stirring, slowly add component B (powder) Continue stirring until a lump free, sloppy, slurry mixture is achieved. If a thicker consistency is required to give the mix better filling properties, some of the liquid component can be withheld. Ensure to mix the solution during application to avoid settling. Pot Life once mixed is approximately 5 hours.
4. Apply two generous coats of the slurry mixture to the entire surface allowing 8 hours drying time between coats
5. In any areas exposed to movement; typically junctions between floors and walls, and larger surface areas, use the Slurry Seal in conjunction with Polyfelt Membrane (a grey polypropylene reinforcing membrane, NOT traditional polyester membrane)
6. Allow 8 hours drying time between coats. Allow the slurry 48 hours drying time, before over coating or tiling.
7. Coverage – 2kg/m²/coat, two coats required. A 5kg kit's effective coverage is 2.5m²

Important Notes

- When applying Slurry Seal onto existing waterproofing systems contact the manufacturer to ensure compatibility.
- Slurry Seal not recommended as a swimming pool coating or as a coating in fibre glass water features or ponds.
- Slurry Seal is not recommended for over coating bitumen systems.

SLURRY SEAL WATERPROOFING / Cementitious Waterproofing Kit

TECHNICAL DATA SHEET

A division of STT Sales PTY (Ltd)

T : 011-892-2917, T : 011-917-9816, F : 011-892-1519, E: info@darachem.co.za
6 Mission Rd, Anderbolt, Boksburg North, P.O. Box 6008, Dunswart 1508