ICI DULUX (PTY) LIMITED

M385-0065

MATERIAL SAFETY DATA SHEET Page: 1

NAME: DULUX TRADE 65 MATT, WHITE

CODE: M385-0065

Date: 2011-12-29

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION NAME: DULUX TRADE 65 MATT, WHITE & TINTS CODES: M385-0065, M385-069X, T385 954X MANUFACTURER: ICI DULUX (PTY) LTD; PAINTS PLACE; DICKENS ROAD; UMBOGINTWINI; 4126. PHONE NUMBERS: 011-861-1000; 031-904-8000. FAX NUMBERS: 011-908-5204; 031-904-8196 EC LABEL: C.A.S. No.: PREPARATION EC No.: UN/SIN No.: NONE EAC: N/A HAZCHEM: HAZARD RATING: N N 2 SAPMA: 3-H-C PIGMENTED WATER BASED EMULSION PAINT WITH POSSIBLE TRACES OF RESIDUAL MONOMER AT PHONE: 031 904 8164 IN EMERGENCY CONTACT: **P MOODLEY**

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS EC CLASSIFICATION: NONE These products contain "NO ADDED LEAD" and measured Lead levels are below 90µg/g NO HAZARDOUS SUBSTANCES PRESENT See Section 15 for full text of R (risk) and S (safety) phrases. RL = recommended limit; *S = skin absorption

SECTION 3. HAZARDS IDENTIFICATION

SAPMA HEALTH RATING: 3-SLIGHT - Irritation or minor reversible injury possible.

INHALATION: May be irritating to sensitive individuals.

SKIN: May be irritating.

EYES: Irritating.

INGESTION: Irritating.

NO CARCINOGENIC, MUTAGENIC OR GENETIC EFFECTS ESTABLISHED

May have short-term environmental effects. Contain, monitor & remove.

SECTION 4.	FIRST AID MEASURES
INHALATION:	Move to fresh air. In case of discomfort seek medical attention.
SKIN:	Wash with plenty of soap and water. Remove contaminated clothing.
	If any discomfort persists seek medical attention.
EYES:	Rinse immediately with plenty of water. Seek medical advice if symptoms persist.
INGESTION:	Give plenty of water or milk. Induce vomiting if patient is conscious. Call doctor.

- SECTION 5. FIRE FIGHTING MEASURES Non-flammable. Keep containers cool with water spray to prevent pressure build-up.
- SECTION 6. ACCIDENTAL RELEASE MEASURES SEE ALSO SECTIONS 5,8 & 13 CONTAIN & COLLECT. KEEP OUT OF DRAINS & SEWERS.
- SECTION 7. HANDLING AND STORAGE Store separately from any reactive substances - oxidisers in particular. Keep containers cool.

This MSDS conforms to SABS ISO 11014-1: 1994 (ISO-11014/ANSI Z400.1.1996) OEL's derived from OHS Act Regulations for Dangerous Chemical Substances dated 25 August 1995 (EH-42) SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991).

MATERIAL SAFETY DATA SHEET

NAME: DULUX	X TRADE 65 MATT, WHITE CODES: M385-0065, M370-069X, T370 954X	Date: 2011-12-29	
SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION			
OEL.TWA: > 80	0ppm TYPE: Mixture See Section 2 "Skin"		
SAPMA RATIN	G: 3-H-C PPE: Gloves & suitable eye protection		
INHALATION:	In case of insufficient ventilation, use suitable respiratory protection.		
SKIN:	Use barrier cream and impervious gloves.		
EYES:	Use face shield or goggles. Avoid direct contact.		
INGESTION:	Observe the rules of hygiene. Wash before eating, drinking or smoking.		
GENERAL:	Appropriate hand protection and protective clothing must always be used.		
SECTION 9.	PHYSICAL AND CHEMICAL PROPERTIES		
CHEMICAL CL	ASS: WATER BASED PAINT		
APPEARANCE:	WHITE OR COLOURED LIQUID		

	WINTE ON COLOUNED LIQUID	
pH: Ca 8,5	DENSITY: 1,33 - 1.43	NON-VOLATILE: Ca47%
FLASH POINT: N/A	VOC: <5g/kg	BOILING POINT: 100+
SOLUBILITY:	WATER: Miscible	OIL: Insoluble
PARTITION COEFFICIE	NT (N-OCTANOL/WATER): N/Q	CONDUCTIVITY: N/Q
~		

- SECTION 10.STABILITY AND REACTIVITYSTABILITY:Stable if stored under normal conditions. Hazardous polymerisation will not occur.
- SECTION 11. TOXICOLOGICAL INFORMATION

NO CARCINOGENIC, MUTAGENIC OR GENETIC EFFECTS ESTABLISHED				
LD ₅₀ ORAL: mg/kg	LD ₅₀ SKIN:	mg/kg	LC ₅₀ INHALATION:	mg

- SECTION 12. ECOLOGICAL INFORMATION May have short-term environmental effects. Contain, monitor & remove.
- SECTION 13. DISPOSAL CONSIDERATIONS Use reputable waste disposal contractors. Destroy used containers.

SECTION 14.	TRANSPORT INFORMATION	
UN No.: NONE	PACKING GROUP: N/A	HAZCHEM CODE: N/A
IMO CLASS: N/A		MARINE POLLUTANT CLASS: L

SECTION 15. REGULATORY INFORMATION

- EC INDEX No.: EEC LABEL No. (EINECS/ELINCS):
- S28 After contact with skin, wash immediately with plenty of water
- S38 In case of insufficient ventilation, wear suitable respiratory equipment

SECTION 16. OTHER INFORMATION IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.