



TIMBAVARNISH WATERBASED



PRODUCT USES

Interior and exterior wood finish where a durable coating with a glossy finish is required.

Ideal for interior furniture, built-in cupboards, ceiling beams, skirting, banisters, cupboards doors, door frames, window frames, fascia boards, fencing and garden furniture, except for floors and areas where a hard, abrasion resistant finish is required.



FEATURES AND BENEFITS

Has superior flexibility compared to conventional varnishes - resists cracking and peeling.

Attractive gloss finish enhances the natural beauty of wood.

Nourishes and protects against harmful UV rays.

Quick drying - recoat in 4 hours.

Contains special wood preservatives to protect against dry rot and fungus.

Environmentally friendly.

Solvent free - water clean-up.



PRODUCT INFORMATION

Appearance	High Gloss
Colour	Clear, Light Oak and Dark Oak
Density at 23°C	Approx. : 1.04 kg/L
Solids Content	By weight : Approx. 25% By volume : Approx. 22%
Packaged Viscosity	Viscosity at 23°C : Approx 0.9P
Spreading Rate	Approx 10m ² per litre depending on surface porosity, profile and application method
Recommended DFT per coat	Min. 25µm. Max. 35µm.



APPLICATION INFORMATION

Application conditions	Surface Temperature between 10 - 35°C Relative Humidity between 10 - 85 %
Thinner	Water if required
Drying Time	Touch dry 4 hours (Drying times will be extended during cold, wet or humid conditions)
Recoating Time	18 hours (overnight)
Cleaning of equipment	Clean immediately with water
Substrates	Suitable for application to all types of wooden surfaces

A glossy,
durable wood
protector for
all interior and
exterior wood
surfaces





APPLICATION INFORMATION

Precautions

Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.

Do not apply during cold (below 10°C) or wet weather.

Stir well before use.

Do not apply directly to bare metal surfaces – stop nail holes with wood filler.

Do not apply to wet or damp timber.

It is important to treat the end grain of timber to prevent moisture ingress.

N.B. Woodgard Timbavarnish Waterbased is not recommended for floors or decking.

APPLICATION METHODS

Brush/Roller (short-nap mohair or foam)

Apply first coat thinned by 5% with water to aid penetration on hard wood.

Allow to dry overnight and sand lightly with 320 grit paper.

Apply second coat unthinned.

For maximum protection, apply a third coat, sanding lightly between coats.

Conventional Spray

Thin up to 10% with water.

N.B. Thinning reduces solids, therefore more coats will be needed to produce the same colour, build, gloss and durability.

Coats Required

For new work, apply three coats.

Apply one to two coats for general maintenance.



SURFACE PREPARATION

NEW SURFACES

New surfaces must be clean, dry and well sanded.

For maximum protection, apply three coats, sanding lightly between coats.

PREVIOUSLY VARNISHED SURFACES

Sound varnish must be wiped down with mineral turpentine to remove wax, oil or silicone.

Finally wipe or rinse the surface with clean tap water and detergent.

Sandpaper lightly with 320 grit paper.

Varnish which is cracked and flaked must be stripped to bare wood either by sanding or by the use of **Fixit Double Strength Paint Remover**.

Sand any discoloured areas to fresh wood.

For maximum protection, apply three coats of varnish.



HEALTH AND SAFETY INFORMATION

For detailed safety information refer to Material Safety Data Sheet.

Keep out of reach of children.

Ensure good ventilation during application and drying.

Non-flammable.



ADDITIONAL INFORMATION

Storage Conditions

Store under cool dry conditions.

Disclaimers

For best colour and sheen consistency, it is advisable to use containers of the same batch number, or to mix different batches together in a large container, or to finish in a corner before starting a new container.