

# Dulux Bathroom+

AKZONOBEL STYRENE ACRYLIC COPOLYMER  
A 958-229007/8A

DATA BULLETIN NO. D74  
DATE: July 2011

<b>Product Description</b>	Dulux Kitchen + is an attractive soft sheen finish for bathrooms.	
<b>Product Uses</b>	<ul style="list-style-type: none"> <li>Suitable for interiors that suffer from high condensation. Not suitable for areas that are continually soaked with water, e.g. shower enclosures.</li> </ul>	
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>Attractive soft sheen finish for high condensation areas</li> <li>Moisture and steam resistant – Ideal for high condensation areas</li> <li>Mould resistant – Mouldtec technology</li> <li>Exceptionally durable and washable</li> <li>Preserved air quality - Low VOC, less than 16 g/L</li> </ul>	
<b>Product Information</b>	Appearance	Soft Sheen
	Colour	Pure Brilliant White
	Density at 23°C	Approx. : 1.23 kg/L
	Solids Content	By weight : Approx. 50%
		By volume : Approx. 43%
	Packaged Viscosity	Viscosity at 23°C : Approx 140 KU
	Volatile Organic Compound	White < 16g/L
	Spreading Rate method.	8 to 10 m <sup>2</sup> per litre depending on surface porosity, profile and application method.
	Recommended DFT per coat	Min. 30µm. Max. 45µm.
<b>Application Information</b>	Application conditions	Surface Temperature between 10 - 35°C Relative Humidity between 10 – 85 %
	Application methods	Brush or roller
	Thinner	Thinning not recommended. Ready for use after thorough stirring
	Drying Time	Touch dry 45 minutes (Drying times will be extended during cold, wet or humid conditions)
	Recoating Time	4 hours
	Cleaning of equipment	Clean immediately with water
	Substrates	Suitable for cement plaster, gypsum plaster, concrete, fibre cement, ceiling boards, provided that appropriate preparation and priming is carried out.

	<p><b>Precautions</b></p> <ul style="list-style-type: none"> <li>• Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.</li> <li>• Do not apply directly to bare metal surfaces.</li> <li>• Not suitable for painting radiators or other heated surfaces.</li> <li>• Do not paint when temperatures are below 10°C</li> <li>• Drying times will be extended during wet or cold weather conditions.</li> <li>• Do not apply directly to chalky or friable surfaces</li> <li>• Protect the paint from extreme weather conditions, particularly frost.</li> <li>• Allow at least 24 hours for the paint to fully dry before exposing to condensation.</li> <li>• Paint is not suitable for areas continually soaked with water such as shower enclosures</li> </ul> <p><b>Coats Required</b></p> <ul style="list-style-type: none"> <li>• Apply two to three finishing coats to new surfaces to achieve a closed film and solid colour.</li> </ul>
<p><b>Surface Preparation</b></p>	<p><b>NEW SURFACES</b></p> <p><b>Cement Plaster (non friable), Gypsum Plaster, Composition Boarding, Fibre Cement</b></p> <ul style="list-style-type: none"> <li>• It is recommended that fresh plaster should be allowed one week drying for every 5mm thickness; and longer in cold or damp weather.</li> <li>• Spot-prime metal strips and nail heads with appropriate metal primer.</li> <li>• Prime with DULUX PLASTER PRIMER.</li> <li>• Rough surfaces may be filled with DULUX TRADE FILLERCOAT to create a smooth base of even porosity.</li> </ul> <p><b>Concrete</b></p> <ul style="list-style-type: none"> <li>• Remove any uncured cement, grease, and mould-release agents by high-pressure water blast, or wash with a strong solution of sugar soap. Rinse off thoroughly with clean water.</li> <li>• Prime with DULUX PLASTER PRIMER.</li> </ul> <p><b>PREVIOUSLY PAINTED SURFACES</b></p> <ul style="list-style-type: none"> <li>• Ensure that surfaces are sound and free from dust, dirt, grease and oil. Surfaces must be thoroughly dry - no more than 12% moisture content.</li> <li>• Sand enamel surfaces to provide a key and improve adhesion.</li> <li>• Loose, flaking paint must be completely removed and bare areas spot primed with appropriate primer. It is always good painting practice to rub down existing surfaces with fine sandpaper to remove nibs and dirt particles. Rubbing down also provides a smooth surface for painting.</li> <li>• Mould instructions. To kill lichen and algae growth, scrub with one of the following solutions: either 4:1 water/HTH (chlorine), or 4:1 water/JIK (sodium hypochlorite). Ensure that the areas are completely saturated, and allow the solution to react for a minimum of four (4) hours. Rinse the complete wall surface thoroughly with clean water.</li> </ul> <p><b>Filling</b></p> <ul style="list-style-type: none"> <li>• Fill and repair imperfections with the appropriate FIXIT filler and prime with DULUX PLASTER PRIMER once the crack filler has dried properly. Failure to do this will result in uneven sheen levels between the repaired and normal areas.</li> </ul>
<p><b>Health and Safety Information</b></p>	<ul style="list-style-type: none"> <li>• For detailed safety information refer to Material Safety Data Sheet.</li> <li>• Keep out of reach of children.</li> <li>• Ensure good ventilation during application and drying.</li> <li>• Non-flammable</li> </ul>

<b>Additional Information</b>	<b>Packaging Size</b>	1L and 2.5L
	<b>Storage Conditions</b>	Store under cool dry conditions
	<b>Disclaimers</b>	<ul style="list-style-type: none"><li>• For best colour and sheen consistency, it is advisable to use containers of the same batch number, or to mix different batches together in a large container, or to finish in a corner before starting a new container.</li></ul>
	<b>Contact</b>	ICI Dulux (Pty) Ltd. PO Box 123704, Alrode, 1451. 8 Juyn Street, Alrode, Alberton. 1450. Helpline 0860 330 111. T +2711 861-1000. F +2711 864- 6701. E <a href="mailto:info@dulux.co.za">info@dulux.co.za</a> . <a href="http://www.dulux.co.za">www.dulux.co.za</a> . <a href="http://www.akzonobel.com">www.akzonobel.com</a>