

SPECIFICATIONS

ELECTRICAL	120V	
WATER CAPACITY	1.25GAL	5 L (Unlimited)
OPERATING PRESSURE	Up to 80 PSI	5.5 BAR
ELEMENTS	2 - 1200 watt each (1 spare)	
IRON STANDARD	2100IR - 7' steam hose	
IRON OPTIONAL	2150IR - 11.5' steam hose	
STEAM BRUSH OPTIONAL	3800IA - 8.5' steam hose	
POWER CONSUMPTION	17 amps, 20-amp plug required	
TANK CONSTRUCTION	Stainless steel	
LOW WATER INDICATOR	Standard	
LOW WATER INDICATOR STEAM CONNECTOR TYPE	Standard Quick-release	
	otanida. d	17.2 kg (w/ out iron)
STEAM CONNECTOR TYPE	Quick-release 38 lb (w/ out	17.2 kg (w/ out iron) 20.8 kg
STEAM CONNECTOR TYPE	Quick-release 38 lb (w/ out iron) 46 lb	ř
STEAM CONNECTOR TYPE NET WEIGHT SHIPPING WEIGHT	Quick-release 38 lb (w/ out iron) 46 lb 11.5" x 11" x 39"	20.8 kg
STEAM CONNECTOR TYPE NET WEIGHT SHIPPING WEIGHT PRODUCT DIMENSIONS	Quick-release 38 lb (w/ out iron) 46 lb 11.5" x 11" x 39"	20.8 kg 29 x 28 x 99 cm 105.5 x 40.5 x 46 cm
STEAM CONNECTOR TYPE NET WEIGHT SHIPPING WEIGHT PRODUCT DIMENSIONS SHIPPING DIMENSIONS	Quick-release 38 lb (w/ out iron) 46 lb 11.5" x 11" x 39" 41.5" x 16" x 18"	20.8 kg 29 x 28 x 99 cm 105.5 x 40.5 x 46 cm

9000IS

PROFESSIONAL AUTOMATIC STEAM IRON STATION

The 9000IS provides continuous steam for an unlimited amount of time when it's hooked up to a direct water line or with the available 2 gallon water container. There's no more downtime waiting for the boiler to re-pressurize. The 9000IS is the perfect choice for environments that require large volumes of uninterrupted steam.

The 9000iS excels at producing quality, dry, pressurized steam. Pressurized steam is the fastest and most effcient way of ironing. It allows the fibers of the fabric to be softened quicker, with the weight and heat of the iron laying the fibers down flat. This creates the crisp and clean finish demanded by professionals.

IT'S ALL ABOUT THE STEAM



PRESSURE GAUGE





771

BLOW DOWN VALVE











BOILER TANK
2 YEAR WARRANTY



THERMOSTAT RESET



5.5 BAR PRESSURE



DIRECT WATER FEED





