

# Duall-88 All Purpose Cement

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 01/02/2018

Date of issue: 01/02/2018

Supersedes Date: 01/06/2017

Version: 1.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Duall-88 All Purpose Cement

**Synonyms:** Polychloroprene Adhesive Blend/Compound

**1.2. Intended Use of the Product:** No additional information available

**1.3. Name, Address, and Telephone of the Responsible Party**

#### Company

RH Products Co., Inc.

308 Old High Street

Acton, MA USA 01720

Information Telephone Number: 1-978-897-8000

### 1.4. Emergency Telephone Number

**Emergency Number** : 1-800-535-5053 INFOTRAC; 1-352-323-3500 INFOTRAC International

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### Classification (GHS-US)

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Muta. 2 H341

Repr. 2 H361

STOT SE 3 H336

STOT RE 2 H373

### 2.2. Label Elements

#### GHS-US Labeling

#### Hazard Pictograms (GHS-US)



#### Signal Word (GHS-US)

: Danger

#### Hazard Statements (GHS-US)

: H225 - Highly flammable liquid and vapor.  
H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H341 - Suspected of causing genetic defects.  
H361 - Suspected of damaging fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.

#### Precautionary Statements (GHS-US)

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, lighting, ventilating equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, spray.  
P264 - Wash hands, forearms, and exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear eye protection, protective clothing, protective gloves.  
P302+P352 - If on skin: Wash with plenty of water.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated

# Dual-88 All Purpose Cement

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center if you feel unwell.  
P321 - Specific treatment (see Section 4).  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>) to extinguish.  
P391 - Collect spillage.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P235+P405 - Keep cool. Store locked up.  
P501 - Dispose of contents/container according to local, regional, national, and international regulations.

### 2.3. Other Hazards

Aquatic Acute 1

Aquatic Chronic 1

H410 - Very toxic to aquatic life with long lasting effects.

P273 - Avoid release to the environment.



GHS09

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Toluene	(CAS No) 108-88-3	37.8	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
n-Heptane	(CAS No) 142-82-5	32.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Proprietary Component A	Proprietary*	14.4	Muta. 2, H341
Ethyl acetate	(CAS No) 141-78-6	8	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Acetone	(CAS No) 67-64-1	3.5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Proprietary Component B	Proprietary*	2.3	Not classified

# Dual-88 All Purpose Cement

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proprietary Component C	Proprietary*	1.9	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317 STOT SE 3, H335
-------------------------	--------------	-----	--

\*The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Full text of H-phrases: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** Using proper respiratory protection, immediately move the exposed person to fresh air. Assure fresh air breathing. Call a physician if symptoms occur.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Causes skin irritation. Causes serious eye irritation. Vapors may cause drowsiness and dizziness. Exposure may produce an allergic reaction.

**Symptoms/Injuries After Inhalation:** High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** May cause damage to organs through prolonged or repeated exposure. May cause damage to central nervous system, liver, and kidneys. Suspected of damaging fertility or the unborn child. Suspected of causing genetic defects.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

**Reactivity:** Reacts violently with oxidants causing fire and explosion hazard.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Do not get water inside containers. Do not apply water stream directly at source of leak. Fight fire from safe distance and protected location.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe vapour or mist.

#### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

# Dual-88 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Emergency Procedures:** Ventilate area. Eliminate ignition sources. Stop leak if safe to do so.

## 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

## 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Use only non-sparking tools.

## 6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place.

**Incompatible Products:** Strong acids. Strong bases. Strong oxidizers.

### 7.3. Specific End Use(s):

No additional information available

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

n-Heptane (142-82-5)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA ACGIH	ACGIH STEL (ppm)	500 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	85 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (ppm)	440 ppm
USA IDLH	US IDLH (ppm)	750 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA IDLH	US IDLH (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
Acetone (67-64-1)		
USA ACGIH	ACGIH TWA (ppm)	500 ppm
USA ACGIH	ACGIH STEL (ppm)	750 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
USA IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
Ethyl acetate (141-78-6)		
USA ACGIH	ACGIH TWA (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>

# Dual-88 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	400 ppm
-----------------	----------------------	---------

## 8.2. Exposure Controls

### Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Gas detectors should be used when flammable gases/vapors may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits indicated above. All electrical equipment should comply with the National Electric Code. Ensure all national/local regulations are observed.

### Personal Protective Equipment

: Full protective flameproof clothing. Protective goggles. Gloves. Insufficient ventilation: wear respiratory protection.



### Materials for Protective Clothing

: Wear fire/flame resistant/retardant clothing.

### Hand Protection

: Wear chemically resistant protective gloves.

### Eye Protection

: Chemical goggles or safety glasses.

### Skin and Body Protection

: Wear suitable protective clothing.

### Respiratory Protection

: Use NIOSH-approved air-purifying or supplied-air respirator where airborne concentrations of vapor or mist are expected to exceed exposure limits.

### Other Information

: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Amber Color
Odor	: Characteristic Solvent Odor
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: > 35 °C (95.00 °F)
Flash Point	: -7.78 °C ASTM D-56 9/21/2008 (18 °F)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20 °C	: > 1 (heavier than air)
Relative Density	: 0.87 (water = 1)
Solubility	: Insoluble in water.
Partition Coefficient: N-octanol/water	: No data available
Viscosity	: No data available
Lower Flammable Limit	: 1 %
Upper Flammable Limit	: 12 %

### 9.2. Other Information

VOC content : 78 % (5.62 lbs/gal or 674 g/l)

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with oxidants causing fire and explosion hazard.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Ignition sources.
- 10.5. Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

# Dual-88 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

<b>n-Heptane (142-82-5)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	103 g/m <sup>3</sup> (Exposure time: 4 h)
<b>Toluene (108-88-3)</b>	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	8390 mg/kg
ATE (Vapors)	25.70 mg/l/4h
<b>Acetone (67-64-1)</b>	
LD50 Oral Rat	5800 mg/kg
LD50 Dermal Rabbit	15688 mg/kg
LC50 Inhalation Rat	44 g/m <sup>3</sup>
<b>Ethyl acetate (141-78-6)</b>	
LD50 Oral Rat	5620 mg/kg
LD50 Dermal Rabbit	> 20 ml/kg
<b>Proprietary Component A</b>	
LD50 Oral Rat	> 40 g/kg

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Causes serious eye irritation.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Suspected of causing genetic defects.

**Carcinogenicity:** Not classified

<b>Toluene (108-88-3)</b>	
IARC group	3
<b>Proprietary Component A</b>	
IARC group	3

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** High concentration of vapours may induce: headache, dizziness, drowsiness, nausea and vomiting.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.

**Symptoms/Injuries After Eye Contact:** Causes serious eye irritation.

**Symptoms/Injuries After Ingestion:** Ingestion is likely to be harmful or have adverse effects.

**Chronic Symptoms:** May cause damage to organs through prolonged or repeated exposure. May cause damage to central nervous system, liver, and kidneys. Suspected of damaging fertility or the unborn child. Suspected of causing genetic defects.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Very toxic to aquatic life with long lasting effects.

<b>n-Heptane (142-82-5)</b>	
LC50 Fish 1	375.0 mg/l (Exposure time: 96 h - Species: Cichlid fish)
<b>Toluene (108-88-3)</b>	
LC50 Fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)
<b>Acetone (67-64-1)</b>	
LC50 Fish 1	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)

# Dual-88 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EC50 Daphnia 1	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	6210 (6210 - 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 (12600 - 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Ethyl acetate (141-78-6)</b>	
LC50 Fish 1	220 - 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])

## 12.2. Persistence and Degradability

<b>Acetone (67-64-1)</b>	
Persistence and Degradability	Readily biodegradable in water.

## 12.3. Bio accumulative Potential

<b>n-Heptane (142-82-5)</b>	
Log Pow	4.66
<b>Toluene (108-88-3)</b>	
Log Pow	2.65
<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69
Log Kow	-0.24
<b>Ethyl acetate (141-78-6)</b>	
BCF fish 1	30
Log Pow	0.6

12.4. Mobility in Soil: No additional information available

## 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable. RCRA Waste Number: D001.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. In Accordance with DOT

Proper Shipping Name : ADHESIVES containing a flammable liquid  
Hazard Class : 3  
Identification Number : UN1133  
Label Codes : 3  
Packing Group : II  
ERG Number : 128



### 14.2. In Accordance with IMDG

Proper Shipping Name : ADHESIVES  
Hazard Class : 3  
Identification Number : UN1133  
Packing Group : II  
Label Codes : 3  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-D  
MFAG Number : 127  
Marine Pollutant : Yes



### 14.3. In Accordance with IATA

Proper Shipping Name : ADHESIVES  
Packing Group : II  
Identification Number : UN1133  
Hazard Class : 3  
Label Codes : 3  
ERG Code (IATA) : 3L



# Dual-88 All Purpose Cement

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

<b>Dual-88 All Purpose Cement</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard
<b>n-Heptane (142-82-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Toluene (108-88-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>RQ (Reportable quantity, section 304 of EPA's List of Lists) :</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Acetone (67-64-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Ethyl acetate (141-78-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Proprietary Component A</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Proprietary Component B</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Proprietary Component C</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2 US State Regulations

<b>Toluene (108-88-3)</b>	
<b>U.S. - California - Proposition 65 - Developmental Toxicity</b>	WARNING: This product contains chemicals known to the State of California to cause birth defects.
<b>n-Heptane (142-82-5)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Toluene (108-88-3)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Acetone (67-64-1)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Ethyl acetate (141-78-6)</b>	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List	
U.S. - Pennsylvania - RTK (Right to Know) List	

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Revision Date</b>	: 01/02/2018
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.



# Dual-88 All Purpose Cement

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### GHS Full Text Phrases:

Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 2	Flammable liquids Category 2
Muta. 2	Germ cell mutagenicity Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
Skin Sens. 1B	Skin sensitization Category 1B
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*The information above is believed to be accurate and represents the information currently available to us. We however, make no warranty of merchantability or any other warranty, express or implied, with respect to this information, and we assume no liability resulting from its use.*

SDS US (GHS HazCom)