



## **2400 SERIES**

DBCI's 2400 Series is a heavy-duty sheet door suitable for warehouse and freight buildings. The 2400 Series has deep engagement guides, ensuring superior durability and strong, long-lasting performance.












The 2400 Series is wind rated up to 12' wide. The pressure rating increases as the door width decreases.

## **2400 SERIES**

#### HEAVY DUTY ROLL-UP


#### **INTERIOR ELEVATION**



### Entrance Association Association


#### GUIDE DETAIL

#### DOOR ENGAGEMENT




# GUIDE STRIP

#### **GUIDE MOUNTING**







MASONRY MOUNT

STEEL MOUNT

WOOD MOUNT

#### CURTAIN

- 26-gauge galvanized, Grade E hard steel
- 5/8" ribbed corrugation
- Maximum opening size 12' x 14'
- Siliconized polyester WeatherXL<sup>™</sup> paint over prime coat

#### **BOTTOM BAR**

- 6063 T6 aluminum extrusion
- 2" x 1<sup>1</sup>/<sub>2</sub>" galvanized angles
- Bulb astragal
- Stainless steel nuts and bolts

#### **AXLE-DRUM ASSEMBLY**

- 15/16" O.D. steel axle, 14-gauge
- 11-gauge axle on doors over 10' wide
- Utilizes 9.5″, 16-gauge drums
- Shielded steel ball bearings in drums
- Oil tempered torsion springs

#### A.C.E. (ADVANCED CURTAIN ENGAGEMENT) GUIDE SYSTEM

- 14-gauge galvanized steel
- Adjustable bolt on head stop
- Polyethylene wear strip
- Pre-punched holes for lock and attachment fasteners

#### HARDWARE

- Saddle clamps with set fasteners
- 10-gauge slide locks, two per door
- 16-gauge step plate; two per door
- 1⁄4″ steel angle T-bracket
- Aluminum "T" shaped lead stop

#### **OPTIONS**

- Chain hoist 4:1 reduction
- Vision panels (17" x 5")
- Hood
- Steel mounting plates
- Motor operated
- Available in 24 colors, subject to availability and varying lead times









The 2400 Series is wind rated up to 12' wide. The pressure rating increases as the door width decreases.

