

# FASTENERS FOR VISIONS & LOUVRES



**LP01**  
Spare BZP screws for LoPro & Lo-FP AA1 44/6 visions. Raised countersunk. #8 x 44mm sheet metal screw. Phillips head, BZP. (Box Qty 100)



**LP02**  
Spare BZP screws for LoPro DD1 50/6 visions. Raised countersunk. #8 x 50mm sheet metal screw. Phillips head, BZP. (Box Qty 100)



**DL01**  
Spare BZP screws for AFDL, ADL & FLDL louvres. Raised countersunk. #8 x 25mm sheet metal screw. Phillips head, BZP. (Box Qty 100)



**DL02**  
Spare BZP screws for FDLS & DRDL louvres. Raised countersunk. #8 x 19mm sheet metal screw. Phillips head, BZP. (Box Qty 100)



**RT01** (173657)  
Restorix Torx Pin security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 19mm. (Box Qty 100)



**RT02** (173662)  
Restorix Torx Pin security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 25mm. (Box Qty 100)



**RT03** (173692)  
Restorix Torx Pin security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 38mm. (Box Qty 100)



**RT04** (173702)  
Restorix Torx Pin security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 50mm. (Box Qty 100)



**SE01** (171430)  
Snake Eye security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 19mm. (Box Qty 100)



**SE02** (171450)  
Snake Eye security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 25mm. (Box Qty 100)



**SE03** (171490)  
Snake Eye security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 38mm. (Box Qty 100)



**SE04** (171520)  
Snake Eye security screw. Self-tapping thread, pan head. A2 stainless steel. 4.2 x 45mm. (Box Qty 100)



**SE05** (171530)  
Snake Eye security screw. Self-tapping thread, countersunk head. A2 stainless steel. 4.2 x 50mm. (Box Qty 100)



**CH01** (175265)  
Clutch Head one way security screw. Self-tapping thread, oval clutch head. A2 stainless steel. 4.2 x 38mm. (Box Qty 100)



**RT10** (199810)  
Restorix Torx Pin driver bit. T-20H. (Box Qty 1)



**SE10** (199532)  
Snake Eye driver bit. SP-8. (Box Qty 1)

A2 = Grade 304  
A4 = Grade 316

# ANEMOSTAT HM-CLIPS

Hollow Metal door clips can be used in hollow metal doors, and replace the need for reinforcing channel in all Anemostat vision frames and louvres when fitted to 44mm thick doors. They are manufactured from 20GA cold rolled steel. The clip is inserted between the door skins with the barbed sides outside the door skin, and then snapped into place, fitting flush with the door cut-out. The number of clips required will depend on the size of the aperture. Please note that when using HM-Clips with LoPro vision frames extra caution should be taken to ensure door cut-out is exact. Do not oversize the cut-out.

Material: 20GA cold rolled steel.  
Purpose: Holds door skins apart without need for reinforcing channel.  
Door thickness: For 44mm thick door only.  
**HM-CLIP** (Box Qty 50)

