

ELECTROMAGNETS & ACCESSORIES

A selection of products from our access control range is shown below. These products will suit inward and outward opening single leaf and double leaf applications, on doors that swing in one direction only. They include basic stand-alone keypads and proximity access control systems. Such products facilitate in controlling access of people into and egress out of buildings; they are not security products. A basic system will comprise an electromagnet, keypad entry and remote button entry, power supply, egress button and emergency escape button. To ensure correct operation, doors should be fitted with a self-closing device e.g. overhead door closer as shown on pages 124-128. Battery back-up is also available to guarantee continued operation in the case of a failure in the power supply. This is a small selection of products from our access control range and there are many other products available. Please ask for details.



ZM7010
Slimline single magnet.
12/24V DC monitored.
275kg holding force, SAA finish.
(Box Qty 1)



ZM7011
Slimline double magnet for pairs of doors.
12/24V DC monitored.
275kg holding force, SAA finish.
(Box Qty 1)



ZMBR008
L bracket set.
For slimline single magnet.
To suit outward opening door.
(Box Qty 1)



ZMBR089
Z & L bracket set.
For slimline single magnet.
To suit inward opening door.
(Box Qty 1)



ZPSU1202C
Power supply unit 12V DC 2 Amp.
Battery charging facility, boxed.
(ZB4012 battery not included).
(Box Qty 1)



ZB4012
Battery for battery back-up unit.
12V DC 7 Amp.
Suitable for use with power supply units.
(Box Qty 1)



ZR200
Multi-purpose fire relay.
For fire alarm connection.
12/24V DC.
(Box Qty 1)



ZKP500
Stand alone / proximity keypad.
12V DC with built in proximity reader.
500 user - weather resistant.
Proximity cards not included but available to order.
(Box Qty 1)



ZC6021
White plastic exit button.
1 gang surface mount.
Rocker switch type.
(Box Qty 1)



ZC6019
Green dome exit button.
Flush mounted 1 gang.
Satin stainless steel.
(Box Qty 1)
ZC610.1 shroud (converts to surface mounting).
(Box Qty 1)



ZCP201
Break glass unit surface fix.
Green resettable call point.
Double pole.
(Box Qty 1)



ZFC620/WH
White steel door monitoring contact.
Flush fitting pencil type.
25mm diameter x 33mm, 15mm operating gap.
4 core pre-wired.
With collar for steel door (overcomes door magnetism).
EN50131-2-6 Grade 2, Environmental Class II.
NEW Now tested for use on uninsulated steel fire doors up to 240 minutes integrity, to BS EN 1634-1:2014. Report available.
(Box Qty 10)

All products usually available ex-stock except those marked with *. Call for lead time.
Additional manufacturers carriage charges may apply for * items.
No charge for split boxes, but please try to order boxed quantity multiples where possible.