




ZFLEX CONCEALED DOOR LOOPS

Whereas typical flexible door loops are surface mounted and remain constantly visible, the patented ZFLEX-C uniquely slides into the door and frame completely concealing itself when the door is closed. Designed essentially for hollow metal doors, the ZFLEX-C is a low cost method of having concealed power transfer from the frame to the door. Designed for continuous and butt hinge applications the ZFLEX-C's aesthetic appeal will benefit retrofits and new installations alike.

Stocked with silver anodised aluminium end caps, the ZFLEX-C is 152mm long offering up to 180° opening when used with standard butt hinges. Also available in the range to special order is the standard unit with black end caps, a model with one end fixed for installations with a solid / filled frame and finally extended patterns for pivot doors. All options can be supplied with silver or black end caps.


To fit this product it will be necessary to drill 16mm diameter holes in the edge of the door and the frame stop. Please ensure that the hole in the door does not compromise the structural integrity of the door. It will be necessary to select a location in the frame that avoids the ZFLEX-C making contact with any reinforcement or anchoring brackets in the frame. The electrical wire must slide freely within the armoured cable to avoid flexing and straining.

- Concealed door loop.
- Standard finish silver aluminium.
- Also available in black finish.
- Designed for hollow metal doors.
- Electrical wire slides freely within the armoured cable.
- Durable finish.
- Easy Installation.
- Variable mounting locations.
- Special 6.4mm flexible armoured conduit.
- Up to 180° opening when used with standard hinges.
- 152mm long for use with butt hinges.
- 305mm long for use with pivots, one side extended.
- 457mm long for use with pivots, both sides extended.




FOR DOORS HUNG ON STANDARD BUTT HINGES, 152MM LONG		
REF	DESCRIPTION	BOX QTY
ZFLEX-C-ALU	152mm length with silver anodised aluminium finish end caps	10
ZFLEX-C-BLK	152mm length with black finish end caps	10
ZFLEX-C-ALU-FX*	152mm length with silver anodised aluminium finish end caps (1 side fixed to create complete concealment in the opposing side)	10
ZFLEX-C-BLK-FX*	152mm length with black finish end caps (1 side fixed to create complete concealment in the opposing side)	10


FOR DOORS MOUNTED ON PIVOTS, 305MM AND 457MM LONG		
REF	DESCRIPTION	BOX QTY
ZFLEX-C-ALU-EXT*	305mm length with silver anodised aluminium finish end caps, door side fixed, frame side extended	10
ZFLEX-C-BLK-EXT*	305mm length with black finish end caps, door side fixed, frame side extended	10
ZFLEX-C-ALU-EXT2*	457mm length with silver anodised aluminium finish end caps, door side fixed, both sides extended	10
ZFLEX-C-BLK-EXT2*	457mm length with black finish end caps, door side fixed, both sides extended	10



DOOR CLOSED



DOOR HALF OPEN



DOOR FULLY OPEN

All products usually available ex-stock except those marked with *. Call for lead time. Additional manufacturers carriage charges may apply for * items. No charge for split boxes, but please try to order boxed quantity multiples where possible.