

STAINLESS STEEL LEVER HANDLES

- Fire - Assessed for integrity only use on insulated timber doorsets for a duration up to 60 minutes, and uninsulated steel doorsets for a duration up to 240 minutes, in accordance with BS EN 1634.1. Report 198067 Issue 6 dated 12.09.18 refers.
- Corrosion - Successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007. Report WIL 392103 dated 30.01.18 refers.
- Accessibility - DDA complaint BS 8300 & Doc M.

Z903.4-SSS - 19MM DIAMETER UNSPRUNG

Grade 304 satin stainless steel 19mm diameter lever on 53x4mm concealed fixing unsprung rose with stainless steel inner, to suit doors 38-55mm thick. Includes screw & bolt through fixings. 8mm spindle included.


(Box Qty 1, outer 20)



Z903.7-SSS - 19MM DIAMETER SPRUNG

Grade 304 satin stainless steel 19mm diameter lever on 53x7mm concealed fixing sprung rose with stainless steel inner, to suit doors 38-55mm thick. Includes screw & bolt through fixings. 8mm spindle included.


(Box Qty 1, outer 20)



Z922.7-SSS - 22MM DIAMETER SPRUNG

Grade 304 satin stainless steel 22mm diameter lever on 53x7mm concealed fixing sprung rose with stainless steel inner, to suit doors 38-55mm thick. Includes screw & bolt through fixings. 8mm spindle included.

(Box Qty 1, outer 20)



LRV (Light Reflective Value) for all lever handles, pull handles and door furniture in satin stainless steel finish is 42.63.

0 = perfect absorbing black.

42.63 = ZEROplus SSS door furniture.

100 = perfect reflecting white.

STAINLESS STEEL ESCUTCHEONS

- Fire - Assessed for integrity only use on insulated timber doorsets for a duration up to 60 minutes, and uninsulated steel doorsets for a duration up to 240 minutes, in accordance with BS EN 1634.1. Report 198067 Issue 6 dated 12.09.18 refers.
- Corrosion - Successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007. Report WIL 392103 dated 30.01.18 refers.

	EURO	BLIND	OVAL	KEY	WASHROOM ▲
53MM DIAMETER X 4MM THICK Concealed fixing escutcheons. Grade 304 stainless steel inner with wood screws. 38mm centres, satin stainless steel.	Z904.4E-SSS	Z904.4B-SSS	Z904.4U-SSS	Z904.4L-SSS	Z904.4W-SSS
	Box Qty 20	Box Qty 20	Box Qty 20	Box Qty 20	Box Qty 5
53MM DIAMETER X 7MM THICK Concealed fixing escutcheons. Grade 304 stainless steel inner with wood screws. 38mm centres, satin stainless steel.	Z904.7E-SSS	Z904.7B-SSS	Z904.7U-SSS	Z904.7L-SSS	Z904.7W-SSS
	Box Qty 20	Box Qty 20	Box Qty 20	Box Qty 20	Box Qty 5

▲ emergency release indicator included (see page 165)

STAINLESS STEEL CYLINDER SHROUD

External cylinder shroud for euro profile cylinder. 12.5mm high, supplied with common 8mm internal escutcheon, with fixings, satin stainless steel. Concealed fixing externally. Bolts pass through internal rose inner and lock at 38mm centres. Clip on cover internally conceals fixings.

Z904.SEC.SSS (Box Qty 1)

