

# STAINLESS STEEL PULL HANDLES

These products have been successfully fire tested to BS EN 1634-1:2014 on steel doors up to 240 minutes integrity. Copy of WF Assessment Report No 387312 Issue 2 available upon request.

Pull handles have also been successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007 Building Hardware - Corrosion Resistance. Report No WIL 392103 dated 30.01.2018 refers.

## 225MM X 19MM DIAMETER SSS PULL HANDLES



**Z905.1-SSS**  
19mm diameter pull handle.  
225mm centres, 65mm proj, bolt through fixing, to suit doors 44-54mm thick, satin stainless steel.  
(Box Qty 1, outer 50)




**Z905.1BB-SSS**  
19mm diameter pull handles.  
225mm centres, 65mm proj, back to back bolt through fixing, secure 4 grub screw fixing, to suit doors 44-54mm thick (and 12mm glass doors), satin stainless steel.  
(Box Qty 1, outer 20)



**Z905.1CF-SSS**  
19mm diameter pull handle.  
225mm centres, 72mm proj, 53x7mm concealed fix roses, with stubby bolts, satin stainless steel (with Z905.5.19 roses).  
(Box Qty 1, outer 50)



**Z905.8-SSS**  
19mm diameter pull handle set.  
225mm centres pull handle, bolt through fixing, 65mm proj with one 300x76x1.5mm plate with radius corners drilled centrally for pull, plate drilled & csk four times, satin stainless steel.  
(Box Qty 10)



**Z905.9-SSS**  
19mm diameter pull handle set.  
225mm centres pull handle, bolt through fixing, 65mm proj with two 300x76x1.5mm plates with radius corners, one drilled centrally for pull, both plates drilled & csk four times, satin stainless steel.  
(Box Qty 10)

Pair of roses with stubby bolts.

**Z905.5.19-SSS**  
**Z905.5.22-SSS**

LRV (Light Reflective Value) = 42.63.

SSS PULL HANDLE SETS COMPONENT BREAKDOWN	
<b>Z905.1-SSS</b>	225x19mm pull handle bolt through fixing
<b>Z901.2-SSS/PH</b>	300x76mm push plate holed centrally, drilled & csk
<b>Z901.2-SSS</b>	300x76mm standard push plate, drilled & csk

## 300MM X 19MM DIAMETER SSS PULL HANDLES



**Z905.3-SSS**  
19mm diameter pull handle.  
300mm centres, 65mm proj, bolt through fixing, to suit doors 44-54mm thick, satin stainless steel.  
(Box Qty 1, outer 50)



**Z905.3BB-SSS**  
19mm diameter pull handles.  
300mm centres, 65mm proj, back to back bolt through fixing, secure 4 grub screw fixing, to suit doors 44-54mm thick (and 12mm glass doors), satin stainless steel.  
(Box Qty 1, outer 20)



**Z905.3CF-SSS**  
19mm diameter pull handle.  
300mm centres, 72mm proj, 53x7mm concealed fix roses, with stubby bolts, satin stainless steel (with Z905.5.19 roses).  
(Box Qty 1, outer 50)

## 300MM X 22MM DIAMETER SSS PULL HANDLES



**Z905.2-SSS**  
22mm diameter pull handle.  
300mm centres, 68mm proj, bolt through fixing, to suit doors 44-54mm thick, satin stainless steel.  
(Box Qty 1, outer 50)



**Z905.2BB-SSS**  
22mm diameter pull handles.  
300mm centres, 68mm proj, back to back bolt through fixing, secure 4 grub screw fixing, to suit doors 44-54mm thick (and 12mm glass doors), satin stainless steel.  
(Box Qty 1, outer 20)



**Z905.2CF-SSS**  
22mm diameter pull handle.  
300mm centres, 75mm proj, 53x7mm concealed fix roses, with stubby bolts, satin stainless steel (with Z905.5.22 roses).  
(Box Qty 1, outer 50)