

CARD FRAME HOLDERS

Grade 5005 aluminium and Grade 304 stainless steel card frames, drilled and countersunk four times for fixing to doors or adjacent walls. The room occupant's name card can be inserted within the card frame and easily changed. Type 1 frames are simple card frame holders but Type 2 frames can be engraved and filled black with up to three digits in Helvetica 1 Line font to denote room numbers. Card frames are also available 3mm polished anodised aluminium (PAA), 3mm polished brass (PB) and 2mm polished stainless steel (PSS) to special order - state card size.

TYPE 1 CARD FRAMES ONLY

ZCF102-SAA 100x75mm, 3mm satin anodised aluminium card frame (Box Qty 5) **ZCF114-SSS*** 100x75mm, 2mm satin stainless steel card frame (Box Qty 5)

Also available 67x50mm and 133x100mm in PAA, PB & PSS to special order.

TYPE 2 CARD FRAMES WITH SIDE PANEL FOR ENGRAVING

ZCF202-SAA* 150x75mm, 3mm satin anodised aluminium card frame (Box Qty 1) **ZCF214-SSS*** 150x75mm, 2mm satin stainless steel card frame (Box Qty 1)

Also available 100x75mm and 200x100mm in PAA, PB & PSS to special order.



SLEEVED LETTER PLATES

NON-FIRE RATED SLEEVED LETTER PLATE

ZP204 Self-attaching sleeved letter plate (two parts). SAA flaps and black plastic frames, with brush internal side to protect against rain and draughts.

Finish: Silver anodised aluminium flaps and black plastic outer frames.

Size: 305x67mm overall outside dimension, 260x44mm aperture, complies with BS 2911

and EN 13724:2013-07.

Telescopic sleeve suits doors 40mm - 80mm thick.

Fixings: Supplied complete with through fixing screws. Fixing centres 275mm. **ZP204** Non-fire rated sleeved letter plate (Box Qty 20)



FIRE RATED SLEEVED LETTER PLATE (ON TIMBER DOORS ONLY)

ZP207 Self-attaching fire rated sleeved letter plate (two parts). SAA flaps and robust all aluminium construction. Fire rated liner provides in excess of half hour integrity under BS 476-20/22 on timber doors only. Smoke seals fitted as standard, Certifire approved Certificate No CF 219. Tested with positive pressure and can be located in any area of the door.

Finish: Silver anodised aluminium flaps as standard, other finishes available to order.

Size: 303x70mm overall outside dimension, 274x58mm aperture complies with BS 2911

and EN 13724:2013-07.

Telescopic sleeve suits doors 40mm - 80mm thick. Supplied complete with through fixing screws.

ZP207 Fire rated sleeved letter plate (Box Qty 20)



ELLEN LETTER PLATE DRAUGHT SEALS

PVC letter plate draught seal with draught excluding brush. Designed to fit on the inside of doors fitted with a conventional letter plate externally (i.e. not a sleeved letter plate). Available with or without flap.

Finish: Available in white and brown.

Fixings:

Size: 82mm high x 340mm wide x 12mm projection. Fixings: Pre-drilled to accept screws and easy to fit.

810201000BBA letter plate seal, white with flap(Box Qty 10)810301000BBA letter plate seal, white without flap(Box Qty 10)810202000BBA letter plate seal, brown with flap(Box Qty 10)810302000BBA letter plate seal, brown without flap(Box Qty 10)



FIRE RATED ALUMINIUM LETTER PLATES

Aluminium letter plate assembly to suit fire rated doors up to 30 minutes, with fire attack from either face. The set includes external letter plate, internal flap and integral PVC encased intumescent aperture liner. Available to suit doors of different thicknesses; 42-47mm thick, 47-52mm thick and 52-57mm thick. Internal security catch ZLP11-BSS available to order separately, see opposite.

Finish: Satin anodised aluminium. Other finishes available to special order. Size: 312x80mm overall outside dimension. Aperture size 250x40mm.

Fixings: Supplied complete with fixing bolts. To be fitted between 250mm and 1700mm from floor level.

Fire rating: 30 minutes on timber and steel doors. Certifire approved, Certificate No CF 255. **ZLP06-44-SAA**Fire rated letter plate set for 42-47mm thick doors (Box Qty 1) **ZLP06-54-SAA***Fire rated letter plate set for 47-52mm thick doors (Box Qty 1)

Fire rated letter plate set for 52-57mm thick doors (Box Qty 1)

