

ZERO 6.4mm LOW FLAT THRESHOLDS

Sizes: 914mm (3 ft), 1219mm (4 ft), 1829mm (6 ft), 2134mm (7 ft), 3048mm (10 ft). Other sizes available to order, maximum 3048mm.

Finishes: A=mill aluminium, B=self colour brass (aka US bronze), D=dark bronze anodised, E=epoxy, STST=stainless steel and V3=full body strength where indicated.


Availability: usually ex-stock except items marked with an asterisk, which are to special order (3-5 weeks) depending on quantity. NH = No Holes.

Corrosion: Zero flat thresholds have been successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007 Building Hardware - Corrosion Resistance. Report No WIL 392103 dated 30.01.2018 refers.




64A

63mm wide x 6.4mm low-profile plain grooved threshold.
64A Aluminium, mill finish




63A

76mm wide x 6.4mm low-profile plain grooved threshold.
63A Aluminium, mill finish



544A

102mm wide x 6.4mm low-profile plain grooved threshold.
544A Aluminium, mill finish




545A, 545D

127mm wide x 6.4mm low-profile plain grooved threshold.
545A Aluminium, mill finish
545D* Dark bronze anodised




545B

127mm wide x 6.4mm low-profile plain grooved threshold.
545B* Brass, self colour



546A

152mm wide x 6.4mm low-profile plain grooved threshold (undrilled). Supplied NH standard.
546A Aluminium, mill finish



547A

178mm wide x 6.4mm low-profile plain grooved threshold (undrilled). Supplied NH standard.
547A Aluminium, mill finish



548A

203mm wide x 6.4mm low-profile plain grooved threshold (undrilled). Supplied NH standard.
548A Aluminium, mill finish

For under door seals to be used in conjunction with these thresholds please refer to pages 34-37.