

## DOOR HOLDERS

Combination floor fixing cylindrical door holder with lock down facility. Operates as a conventional doorstop, or holds the door open by depressing, passing the door over it and releasing. Manufactured from Grade 316 satin stainless steel. Supplied complete with multi purpose rawl plugs and stainless steel screws. The buffer can be locked down to become inoperative by depressing and a quarter turn.

Faceplate 45x45x2.5mm. Cylinder 32mm dia x 52mm.

**Z335** Satin stainless steel

(Box Qty 1)

Combination floor fixing cylindrical door holder (no lock down facility). Operates as a conventional doorstop, or holds the door open by depressing, passing the door over it and releasing. Manufactured from Grade 316 satin stainless steel. Supplied complete with multi purpose rawl plugs and stainless steel screws. Tested to 100,000 cycles. Faceplate 45x45x2.5mm. Cylinder 32mm dia x 52mm.

Z345

Satin stainless steel

(Box Qty 1)

Cylindrical door stop and holder (no lock down facility) to suit doors up to 55mm thick. Holds the door open between the stops by depressing the first stop, passing the door over it and releasing. Manufactured from Grade 316 satin stainless steel. Supplied complete with multi purpose rawl plugs and stainless steel screws. Faceplate 125x45x2.5mm. Cylinder 32mm dia x 52mm.

**Z370** 

Satin stainless steel

(Box Qty 1)

Cylindrical door stop and holder with lock down facility to suit doors up to 55mm thick. Holds the door open between the stops by depressing the first stop, passing the door over it and releasing. Manufactured from Grade 316 satin stainless steel. Supplied complete with multi purpose rawl plugs and stainless steel screws. The buffer can be locked down to become inoperative by depressing and a quarter turn. Faceplate 125x45x2.5mm. Cylinder 32mm dia x 52mm.

**Z**390

Satin stainless steel

(Box Qty 1)

Two-part door buffer and holder. The main black rubber part fixes to the door restraint or wall, and the small grey nylon insert plug fits to the outside of the door. The plug engages in the main part and holds the door open until released. 60mm projection, 40mm diameter base.

Z440

Black rubber/grey nylon insert


(Box Qty 10)

Kick down holders are mounted to the bottom of the door on the push side and hold the door open with a reliable grip on the floor. The units provide simple hold and release, activated with a touch of the foot. A stainless steel spring holds the arm in the vertical position when not in use. The arm and plates are manufactured from solid cast aluminium and the rubber bumper is held on with a screw. The arm measures 102mm and has a door to floor clearance of 51mm or less.

**Z460R** 

Kick down door stop, silver grey finish

(Box Qty 10)



Z1402 (582)

Black

(Box Qty 10)

Pipe stop and holder of heavy duty construction for use in schools, institutions etc. All stainless steel components with rubber buffer. Floor portion is solid 25mm diameter x 280mm long stainless steel rod which is secured in cement. The rubber bumper plate is fixed to the door and hits the floor mounted pipe when used as a stop. The door is hooked to the floor portion with stainless steel hook when used as a holder. The door hook rotates out of the way when not in use.

Z1804

Stainless steel US32D

(Box Qty 1)

Hook and eye gravity door holder. Main part fixes to restraint or wall, and small hook fits to outside of door. The main part rides up over the hook and holds the door open until released.

Z2108

Satin chrome plated brass

(Box Qty 10)

















