

ZERO DOOR RESTRAINTS

HOOP POST DOOR RESTRAINERS

Goal post door holder fabricated from mild steel tubular section with radiused top corners, coated black as standard but can be supplied powder coated to match RAL numbers. Manufactured from 42mm diameter tubular mild steel zinc plated. Overall width 650mm, overall height 1150mm with 8mm diameter pins at base for letting into concrete. These products are not drilled as standard for buffers to allow on-site fixing in desired position.

Material: Mild steel zinc plated standard or stainless steel to order.
 Width: 650mm overall.
 Height: 1150mm overall including 300mm for building in.
 Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).
 Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z124P.1	With Z440 black door buffer/holder
Z124P.2	With Z1402/582 black birds beak holder
Z124P.3	Without buffer or beak holder



Z124P.3 illustrated

Goal post door holder fabricated from mild steel tubular section with radiused top corners, coated black as standard but can be supplied powder coated to match RAL numbers. Manufactured from 42mm diameter tubular mild steel zinc plated. Overall width 650mm, overall height 850mm, with 100mm diameter x 5mm thick plates at base each drilled with four 10mm holes for flange surface fixing to concrete. These products are not drilled as standard for buffers to allow on-site fixing in desired position.

Material: Mild steel zinc plated standard or stainless steel to order.
 Width: 650mm overall.
 Height: 850mm overall.
 Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).
 Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z124F.1	With Z440 black door buffer/holder
Z124F.2	With Z1402/582 black birds beak holder
Z124F.3	Without buffer or beak holder



Z124F.3 illustrated

Other widths and heights available on request.

NYLON SADDLE WASHER

40mm diameter x 14mm high black washer to provide flat surface for mounting door buffers on 42mm diameter tube.

Z125 (Box Qty 50)



HOOP POST DOOR RESTRAINERS WITH SMALL INFILL PANEL

Radiused tubular post door holder fabricated from mild steel, coated black as standard but can be supplied powder coated to match RAL numbers. Manufactured from 42mm diameter tubular mild steel zinc plated. Overall width 400mm, overall height 1550mm with 8mm diameter pins at base for letting into concrete. Steel infill plate fixed at top, with 5mm hole drilled centrally for Z440 only.

Material: Mild steel zinc plated standard or stainless steel to order.
 Width: 400mm overall.
 Height: 1550mm overall including 300mm for building in.
 Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).
 Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z135P.1	With Z440 black door buffer/holder
Z135P.3	Without buffer



Z135P.3 illustrated

Radiused tubular post door holder fabricated from mild steel, coated black as standard but can be supplied powder coated to match RAL numbers. Manufactured from 42mm diameter tubular mild steel zinc plated. Overall width 400mm, overall height 1250mm, with 100mm diameter x 5mm thick plates at base each drilled with four 10mm holes for flange surface fixing to concrete. Steel infill plate fixed at top, with 5mm hole drilled centrally for Z440 only.

Material: Mild steel zinc plated standard or stainless steel to order.
 Width: 400mm overall.
 Height: 1250mm overall.
 Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).
 Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z135F.1	With Z440 black door buffer/holder
Z135F.3	Without buffer



Z135F.3 illustrated

Other widths and heights available on request.