

## ZERO CYCLE SUPPORTS

## **90 DEGREE CYCLE SUPPORT POSTS**

Single 90 degree cycle support fabricated from mild steel, coated black as standard but can be supplied powder coated to match RAL numbers. Manufactured from 40mm square section mild steel, zinc plated. Overall width 800mm, overall height 1150mm with 8mm dia pins at base for letting into concrete, with one 100x100x5mm square wall plate, drilled with four 10mm holes.

Material: Mild steel zinc plated standard or stainless steel to order.

Width: 800mm overall.

Height: 1150mm overall including 250mm for building in.

Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).

Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z160P.0	1150mm high with pins to build at base



7160P0 illustrated

Single 90 degree cycle support fabricated from mild steel, coated black as standard but can be supplied powder coated to match RAL numbers. Manufactured from 40mm square section mild steel, zinc plated with two 100x100x5mm square plates for wall and ground fixing each drilled with four 10mm holes. Overall width 800mm, overall height 900mm.

Material: Mild steel zinc plated standard or stainless steel to order.

Width: 800mm overall. Height: 900mm overall.

Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).

Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z160F.0	900mm high with two square base plate flanges

Other widths and heights available on request.



Z160F.0 illustrated

## **TUBULAR 90 DEGREE CYCLE SUPPORT POSTS**

Single 90 degree cycle support fabricated from mild steel tubular section, coated black as standard but can be supplied powder coated to match RAL numbers.

Manufactured from 42mm diameter tube mild steel, zinc plated. Overall width 800mm, overall height 1150mm with 8mm dia pins at base for letting into concrete, with one 100x5mm circular wall plate, drilled with four 10mm holes.

Material: Mild steel zinc plated standard or stainless steel to order.

Width: 800mm overall.

Height: 1150mm overall including 250mm for building in.

Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).

Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z165P.0	1150mm high with pins to build at base



Z165P.0 illustrated

Single 90 degree cycle support fabricated from mild steel tubular section, coated black as standard but can be supplied powder coated to match RAL numbers.

Manufactured from 42mm diameter tube mild steel, zinc plated with two 100x5mm circular plates for wall and ground fixing each drilled with four 10mm holes. Overall width 800mm, overall height 900mm.

Material: Mild steel zinc plated standard or stainless steel to order.

Width: 800mm overall. Height: 900mm overall.

Finish: Standard finish Black (/BLK), and Zinc (/ZNC) or Stainless Steel (/SS).

Can be supplied powder coated to RAL numbers.

REF	DESCRIPTION
Z165F.0	900mm high with two circular base plate flanges

Other widths and heights available on request.



Z165F.0 illustrated