


# ZERO RABBETED THRESHOLDS

Sizes: 914mm (3 ft), 1219mm (4 ft), 1829mm (6 ft), 2134mm (7 ft), 3048mm (10 ft). Other sizes available to order, maximum 3048mm.


Finishes: A=mill aluminium, B=self colour brass (aka US bronze), D=dark bronze anodised, E=epoxy, STST=stainless steel and V3=full body strength where indicated. Replacement black flipper gasket 486N available.


Availability: usually ex-stock except items marked with an asterisk, which are to special order (3-5 weeks) depending on quantity.


Corrosion: Zero rabbeted thresholds have been successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007 Building Hardware - Corrosion Resistance. Report No WIL 392103 dated 30.01.2018 refers.




















# 579A

127mm wide x 19.1mm high latchtrack rabbeted threshold with black neoprene seal, for use with pullman panic bolts. 579A Aluminium, mill finish

# 563A

91mm wide x 22mm high rabbeted threshold with black neoprene seal.

563A Aluminium, mill finish

## 565A

123mm wide x 22mm high rabbeted threshold with black neoprene seal.

565A Aluminium, mill finish

#### 267A

55 mm wide x 16 mm high rabbeted half threshold with black neoprene seal.

267A Aluminium, mill finish

#### 627A

49 mm wide x 12.7 mm high half threshold with black neoprene seal.

627A Aluminium, mill finish

# 628A

75mm wide x 12.7mm high half threshold with black neoprene seal.

628A Aluminium, mill finish

## 524A

74mm wide x 22mm high half threshold with black double neoprene seal.

524A Aluminium, mill finish

#### 561A

114mm wide x 25mm high bulkhead rabbeted threshold with black neoprene seal. 561A Aluminium, mill finish