

KISO EPDM SELF-ADHESIVE OEM SEALS EXTENDED RANGE

A wide range of extruded EPDM self-adhesive sealing systems. Various profiles and sizes are available to suit all non-fire rated applications. They are PSA backed so all are quick, easy and clean to apply to frame head and jambs. Please note that the surface preparation must be clean, warm, dry, grease free and dust free. The application temperature must be higher than 0°C.

EPDM = Ethylene Propylene Diene Monomer.

CUT LENGTHS AVAILABLE. (CANNOT GUARANTEE CONTINUOUS LENGTH)



KISO D SEAL

Extruded EPDM cellular rubber weather sealing strip with "D" profile. With PSA pressure sensitive adhesive tape to back. NOT suitable for use on fire rated doors.

- Material: Flexible EPDM.
- Sizes: 6, 7, 8, 10, 12, 17mm high. 8, 9, 12, 14, 18, 21mm wide. All stocked.
- Coil size: Varies depending on seal thickness.
- Colours: Black /BLK, brown /BRN, white /WHT. Stock colours in table.
- Temperature: Temperature resistance -50°C to +90°C.
- Applications: Metal doors, metal cupboards, timber windows and doors. For larger gaps.



REF	HEIGHT	WIDTH	COIL LENGTH	COLOUR	FRAME GAP	BOX QTY
D-0608/BLK	6mm	8mm	160m	Black	3-5mm	3
D-0709/BLK NEW	7mm	9mm	120m	Black	4-6mm	3
D-0808/BLK NEW	8mm	8mm	120m	Black	5-7mm	3
D-1012/BLK	10mm	12mm	70m	Black	7-9mm	3
D-1018/BLK NEW	10mm	18mm	80m	Black	7-9mm	2
D-1214/BLK	12mm	14mm	100m	Black	9-11mm	1
D-1721/BLK	17mm	21mm	50m	Black	13-16mm	1

KISO P SEAL

Extruded EPDM cellular rubber weather sealing strip with "P" profile. With PSA pressure sensitive adhesive tape to back. NOT suitable for use on fire rated doors.

- Material: Flexible EPDM.
- Sizes: 5.5mm high only.
- Coil size: 100 metres and 160 metres.
- Colours: Black /BLK, brown /BRN, white /WHT. Stock colours in table.
- Temperature: Temperature resistance -50°C to +90°C.
- Applications: Metal and timber windows and doors. For medium gaps.



REF	HEIGHT	WIDTH	LENGTH	COLOUR	FRAME GAP	BOX QTY
P-5509/BLK	5.5mm	9mm	160m	Black	3-5mm	3
P-5509/BRN	5.5mm	9mm	160m	Brown	3-5mm	3
P-5509/WHT	5.5mm	9mm	100m	White	3-5mm	6

KISO 141 SEAL

Extruded EPDM cellular rubber weather sealing strip. With PSA pressure sensitive adhesive tape to back. Ensures both water and air tightness between frame, glass and beads. As used in the Scandinavian window industry for over 30 years. NOT suitable for use in fire rated applications.

- Material: Flexible EPDM.
- Sizes: 2, 3, 4, 5mm high. 8, 9, 10, 12, 15mm wide.
- Coil size: Varies depending on seal thickness.
- Colours: Black /BLK, brown /BRN, white /WHT. Stock colours in table.
- Temperature: Temperature resistance -50°C to +90°C.
- Applications: Metal and timber windows and doors.
- Note: Number of ridges may vary depending on size and colour.



REF	HEIGHT	WIDTH	LENGTH	COLOUR	BOX QTY
141.0208/BLK	2mm	8mm	225m	Black	6
141.0309/BLK	3mm	9mm	150m	Black	6
141.0309/WHT	3mm	9mm	150m	White	6
141.0312/BLK	3mm	12mm	150m	Black	6
141.0315/BLK	3mm	15mm	100m	Black	6
141.0409/BLK	4mm	9mm	125m	Black	6
141.0409/BRN	4mm	9mm	125m	Brown	6
141.0409/WHT	4mm	9mm	125m	White	6
141.0510/BLK	5mm	10mm	100m	Black	6