

SLIMPORT CIRCULAR METAL VISION FRAMES

SLIMPORT TWO PART RING SET TO SUIT XX DOOR THICKNESS - (GLASS AND GLAZING TAPE SUPPLIED SEPARATELY BELOW)

REF	FINISH	CODE	XX=.40	XX=.44	XX=.50	XX=.54
SP250 250MM CUT-OUT 200MM VISIBLE LIGHT 223MM GLASS DIAMETER 785MM CIRCUMFERENCE 285MM OUTSIDE FRAME	Zinc plated mild steel	SP250.XX-GV	✓	✓	✓	✓
	Chrome pearlite silver ▲	SP250.XX-CP	-	✓	✓	✓
	Satin stainless steel	SP250.XX-SS	✓	✓	✓	✓
	Polished stainless steel	SP250.XX-PS*	✓	✓	✓	✓
SP350 350MM CUT-OUT 300MM VISIBLE LIGHT 323MM GLASS DIAMETER 1100MM CIRCUMFERENCE 385MM OUTSIDE FRAME	Zinc plated mild steel	SP350.XX-GV	✓	✓	✓	✓
	Chrome pearlite silver ▲	SP350.XX-CP	-	✓	✓	✓
	Satin stainless steel	SP350.XX-SS	✓	✓	✓	✓
	Polished stainless steel	SP350.XX-PS*	✓	✓	✓	✓
SP450 450MM CUT-OUT 400MM VISIBLE LIGHT 423MM GLASS DIAMETER 1415MM CIRCUMFERENCE 485MM OUTSIDE FRAME	Zinc plated mild steel	SP450.XX-GV	✓	✓	✓	✓
	Chrome pearlite silver ▲	SP450.XX-CP	-	✓	✓	✓
	Satin stainless steel	SP450.XX-SS	✓	✓	✓	✓
	Polished stainless steel	SP450.XX-PS*	✓	✓	✓	✓
SP550 550MM CUT-OUT 500MM VISIBLE LIGHT 523MM GLASS DIAMETER 1729MM CIRCUMFERENCE 585MM OUTSIDE FRAME	Zinc plated mild steel	SP550.XX-GV	-	✓	✓	✓
	Chrome pearlite silver ▲	SP550.XX-CP	-	✓	-	-
	Satin stainless steel	SP550.XX-SS	-	✓	✓	✓
	Polished stainless steel	SP550.XX-PS*	-	✓	-	-

.40 two part ring set to suit 38-42mm (40mm nominal) thick door and 6mm glass (10mm glazing space) see page 91.

.44 two part ring set to suit 42-46mm (44mm nominal) thick door and 6mm glass (10mm glazing space).

.50 two part ring set to suit 47-51mm (49mm nominal) thick door and 6mm glass (10mm glazing space) see page 91.

.54 two part ring set to suit 52-56mm (54mm nominal) thick door and 6mm glass (10mm glazing space).

▲ Note: Chrome pearlite silver finish not suitable for external use. For external, corrosive and coastal applications use stainless steel.

GLASS CIRCLES AND GLAZING TAPES

GT-132	0.8mm thick x 9.5mm wide x 61 metre roll (200ft)	Black closed cell polyvinyl chloride foam
ZPGT-1010/DS	1.0mm thick x 10.0mm wide x 50 metre roll	Black closed cell polyvinyl chloride foam
GT-116	1.6mm thick x 9.5mm wide x 61 metre roll (200ft)	Black closed cell polyvinyl chloride foam
ZPGT-1510/DS	1.5mm thick x 10.0mm wide x 46 metre roll	Black closed cell polyvinyl chloride foam
GT-18	3.2mm thick x 9.5mm wide x 30 metre roll (100ft)	Black closed cell polyvinyl chloride foam
ZPGT-3010/DS	3.0mm thick x 10.0mm wide x 20 metre roll	Black closed cell polyvinyl chloride foam
"CERAMIC TYPE" GLAZING TAPES (FIT TO BOTH SIDES OF GLASS I.E. CIRCUMFERENCE X 2) - AVAILABLE IN COMPLETE ROLLS ONLY		
FS9009 (9782375PSA-WHT)	2.0mm thick x 10.0mm wide x 10 metre long roll	White "ceramic type" glazing tape, PSA backing
FS9009 (9157375PSA-WHT)	4.0mm thick x 10.0mm wide x 10 metre long roll	White "ceramic type" glazing tape, PSA backing
FS9009 (9236375PSA-WHT)	6.0mm thick x 10.0mm wide x 10 metre long roll	White "ceramic type" glazing tape, PSA backing
FS9009 (9782375PSA-BLK)	2.0mm thick x 10.0mm wide x 10 metre long roll	Black "ceramic type" glazing tape, PSA backing
FS9009 (9157375PSA-BLK)	4.0mm thick x 10.0mm wide x 10 metre long roll	Black "ceramic type" glazing tape, PSA backing
FS9009 (9236375PSA-BLK)	6.0mm thick x 10.0mm wide x 10 metre long roll	Black "ceramic type" glazing tape, PSA backing
INTUMESCENT APERTURE LINERS (FOR TIMBER FIRE DOORS - TO FIT INSIDE OF DOOR CUT-OUT I.E. CIRCUMFERENCE) - ORDER IN STOCK LENGTHS ONLY		
FS4004 (40621750PSA/8)	1.6mm thick x 44mm wide x 2438mm long (½ hr)	Intumescent aperture liner, PSA backing
FS4004 (40622125PSA/8)	1.6mm thick x 54mm wide x 2438mm long (1 hr)	Intumescent aperture liner, PSA backing
FS4004 (40621750PSA/4)	1.6mm thick x 44mm wide x 1219mm long (½ hr)	Intumescent aperture liner, PSA backing
FS4004 (40622125PSA/4)	1.6mm thick x 54mm wide x 1219mm long (1 hr)	Intumescent aperture liner, PSA backing

GLASS (FOR FIRE RATED AND NON-FIRE RATED DOORS)	DIAMETER 223MM	DIAMETER 323MM	DIAMETER 423MM	DIAMETER 523MM
6.4mm thick laminated clear safety glass (non-fire rated)	LAM223	LAM323	LAM423	LAM523
7.2mm thick clear GWP safety (½ hr fire rated) see page 95	GWP223	GWP323	GWP423	GWP523*
6mm thick clear fire resistant (½ and 1hr fire rated)	PCT223	PCT323	PCT423	PCT523*
9mm thick laminated clear ceramic (4hr fire rated)	FIR9223	FIR9323	FIR9423	FIR9523*
6.4mm thick laminated opaque glass (non-fire rated)	LAM223/F	LAM323/F	LAM423/F	LAM523/F*
6mm thick frosted fire resistant (½ and 1hr fire rated)	PCT223/F	PCT323/F	PCT423/F	PCT523/F*