

NON-FIRE RATED GLAZING TAPES

When installing our LoPro or Slimport vision frames, glazing tape should be fitted on both sides of the glass and frames. The thickness of the tape will be determined by the thickness of the glass being used and the thickness of the door the frame is being fitted to. When applying the glazing tape, peel it off from the roll and place the exposed adhesive side directly on to the clean surface of the vision frame or glass to be glazed. Do not remove the liner until the glazing tape is in the proper position.

PVC FOAM TAPES WITH SINGLE SIDED SELF-ADHESIVE BACKING

Manufactured in the UK, these polyvinyl chloride foam tapes are supplied with single sided tape, based on an all weather solvent acrylic adhesive system. They are protected with an acrylic liner.

Colour: Black.
 Sizes: Always 10mm wide. Available in five thicknesses, 1mm, 2mm, 3mm, 6mm and 8mm. Roll length varies depending on tape thickness.
 Tape: Single sided (suffix **/SS**).
 Temperature: Service temperature -20°C to +90°C. Application temperature +10°C to +45°C.
 Compression: Recommended compression 25%. Maximum compression 30%. Do not over compress.
 Box quantity: 30 rolls per carton.

REF	DESCRIPTION - SINGLE SIDED TAPES, BLACK	BOX QTY
ZPGT-1010/SS	1.0mm thick x 10mm wide x 50 metre roll, single sided tape	30
ZPGT-2010/SS	2.0mm thick x 10mm wide x 40 metre roll, single sided tape	30
ZPGT-3010/SS	3.0mm thick x 10mm wide x 25 metre roll, single sided tape	30
ZPGT-6010/SS	6.0mm thick x 10mm wide x 15 metre roll, single sided tape	30
ZPGT-8010/SS	8.0mm thick x 10mm wide x 10 metre roll, single sided tape	30



PVC FOAM TAPES WITH DOUBLE SIDED SELF-ADHESIVE BACKING

Also manufactured in the UK, these polyvinyl chloride foam tapes are supplied with double sided tape, based on an all weather solvent acrylic adhesive system. They are protected with an acrylic liner.

Colour: Black.
 Sizes: 10mm or 20mm wide. Available in eight thicknesses, 1mm, 1.5mm, 2mm, 3mm, 4mm, 5mm, 6mm and 8mm. Roll length varies depending on tape thickness.
 Tape: Double sided (suffix **/DS**).
 Temperature: Service temperature -20°C to +90°C. Application temperature +10°C to +45°C.
 Compression: Recommended compression 25%. Maximum compression 30%. Do not over compress.
 Box quantity: 30 rolls per carton.

REF	DESCRIPTION - DOUBLE SIDED TAPES, BLACK	BOX QTY
ZPGT-1010/DS	1.0mm thick x 10mm wide x 50 metre roll, double sided tape	30
ZPGT-1510/DS	1.5mm thick x 10mm wide x 46 metre roll, double sided tape	30
ZPGT-2010/DS	2.0mm thick x 10mm wide x 25 metre roll, double sided tape	30
ZPGT-3010/DS	3.0mm thick x 10mm wide x 20 metre roll, double sided tape	30
ZPGT-3020/DS	3.0mm thick x 20mm wide x 20 metre roll, double sided tape	30
ZPGT-4010/DS	4.0mm thick x 10mm wide x 20 metre roll, double sided tape	30
ZPGT-5010/DS	5.0mm thick x 10mm wide x 12 metre roll, double sided tape	30
ZPGT-6010/DS	6.0mm thick x 10mm wide x 10 metre roll, double sided tape	30
ZPGT-8010/DS	8.0mm thick x 10mm wide x 10 metre roll, double sided tape	30



ANEMOSTAT CLOSED CELL FOAM GLAZING TAPES

Manufactured in the USA, these Anemostat glazing tapes are closed cell polyvinyl chloride foam sealant with pressure sensitive adhesive on two sides, protected with a paper or polyethylene liner.

Colour: Black.
 Sizes: Always 9.5mm wide. Available in four thicknesses, 1/32" (0.8mm), 1/16" (1.6mm), 1/8" (3.2mm), and 1/4" (6.4mm). Roll length varies depending on tape thickness.
 Tape: Double sided, with blue release paper.
 Temperature: Service temperature -20°C to +90°C. Application temperature +7°C to +45°C.

REF	DESCRIPTION - CLOSED CELL FOAM TAPES, BLACK	BOX QTY
GT-132*	0.8mm thick x 9.5mm wide x 200 feet (61m) roll, double sided tape	4
GT-116	1.6mm thick x 9.5mm wide x 200 feet (61m) roll, double sided tape	4
GT-18	3.2mm thick x 9.5mm wide x 100 feet (30m) roll, double sided tape	4
GT-14*	6.4mm thick x 9.5mm wide x 50 feet (15m) roll, double sided tape	4

