

KISO DRY GLAZING TAPES

KISO 141 DRY GLAZING TAPE

Manufactured in Denmark, the KISO 141 profile is an extruded and self-adhesive EPDM cellular rubber sealing strip. It is very popular with timber window manufacturers and enables glass to be mounted quickly, cleanly and simply. It ensures both water and air tightness between frame, glass and beads.

It can also be used on wooden conservatories between insulating glass and fixed frames, as well as between insulating glass and beads. This product has excellent resistance to ozone and very good ageing properties as well as negligible water absorption. KISO 141 has been used in the Scandinavian fenestration industry for over 30 years. Minimum compression 25%, recommended compression 30%.

- Colours: Black (/BLK), brown (/BRN) and white (/WHT). Stock colours shown in table.
- Sizes: Available in different thicknesses and widths. Not all dimensions shown below are available in brown or white. Roll length varies depending on tape thickness.
- Tape: This product is backed with webbed non-stretch self-adhesive tape on one side. It has excellent adhesion on clean dry surfaces free from grease and dust, and is suitable for factory as well as on-site glazing. Units glazed with KISO 141 dry glazing tape are immediately ready for shipment.
- Temperature: Temperature resistance -50°C to +90°C.



REF	DESCRIPTION - DRY GLAZING TAPES	BOX QTY
141.0208/BLK	2.0mm thick x 8mm wide x 225 metre roll, single sided tape (black only)	6
141.0309/BLK	3.0mm thick x 9mm wide x 150 metre roll, single sided tape (black)	6
141.0309/WHT	3.0mm thick x 9mm wide x 150 metre roll, single sided tape (white)	6
141.0312/BLK	3.0mm thick x 12mm wide x 150 metre roll, single sided tape (black only)	6
141.0315/BLK	3.0mm thick x 15mm wide x 100 metre roll, single sided tape (black only)	6
141.0409/BLK	4.0mm thick x 9mm wide x 125 metre roll, single sided tape (black)	6
141.0409/BRN	4.0mm thick x 9mm wide x 125 metre roll, single sided tape (brown)	6
141.0409/WHT	4.0mm thick x 9mm wide x 125 metre roll, single sided tape (white)	6
141.0510/BLK	5.0mm thick x 10mm wide x 100 metre roll, single sided tape (black only)	6

KISO H/PB HOLLOW PROFILE DRY GLAZING TAPE

KISO H/PB is an extruded EPDM cellular rubber glazing tape with hollow profile. This product works in exactly the same way as the KISO 141 dry glazing tape above, except that the hollow pocket enables the seal to be turned at corners and used as continuous perimeter glazing without the need for cutting. Ensures both water and air tightness between frame, glass and beads.

Supplied with PSA pressure sensitive adhesive tape to back. This product has excellent resistance to ozone and very good ageing properties as well as negligible water absorption. As used in the Scandinavian fenestration industry for over 30 years on wooden windows and conservatories. Minimum compression 25%, recommended compression 30%.

- Colour: Black only (/BLK).
- Sizes: Available one size only, 6mm high x 10mm wide.
- Tape: This product is backed with webbed non-stretch self-adhesive tape on one side. It has excellent adhesion on clean dry surfaces free from grease and dust, and is suitable for factory as well as on-site glazing. Units glazed with KISO H/PB dry glazing tape are immediately ready for shipment.
- Temperature: Temperature resistance -50°C to +90°C.



REF	DESCRIPTION - HOLLOW DRY GLAZING TAPES	BOX QTY
H/PB/BLK	6.0mm thick x 10mm wide x 115 metre roll, single sided tape (black only)	3

SILICONE GLAZING CHANNELS

Designed for use with our LoPro, Lo-FP and Slimport 450mm diameter and above pre-fabricated metal vision frames shown on pages 74-75, 83 and 88-91, this glazing channel is manufactured from silicone. Simple to cut and easy to install, there is no need to bother with self-adhesive tapes again. The integral 'lip' along the top edge of the gasket sits on the vision frame bevel to provide a weather-tight seal against rain seepage on external applications. Aesthetically it also blends in with the frame bevel resulting in a neat and pleasing assembly.

GC10/6 is designed to accommodate 6mm (and 6.4mm) thick glass in LoPro, Lo-FP and Slimport vision frames (except circles with cut-outs less than 450mm) with a 10mm glazing pocket being used on 44mm thick doors, and will prevent the ingress of water. GC16/6 suits 6mm (and 6.4mm) thick glass in standard LoPro and Lo-FP vision frames with a 16mm glazing pocket being used on 50mm thick doors. The standard colour is black, but it may be available in other colours to special order depending on quantity.

- Material: Silicone.
- Colour: Standard colour black, other colours available to special order.
- Glass size: To suit 6mm and 6.4mm glass.
- Fire rating: For use on non-fire rated doors.
- Temperature: Suitable for use from -40°C to +80°C.
- Coil length: 25 metres.
- Box quantity: 1 coil per box.

GC10/6

10mm wide.
6mm glazing pocket.
25 metre coil



GC16/6

16mm wide.
6mm glazing pocket.
25 metre coil



All products usually available ex-stock except those marked with *. Call for lead time.
Additional manufacturers carriage charges may apply for * items.
No charge for split boxes, but please try to order boxed quantity multiples where possible.