

STAINLESS STEEL LEVER HANDLES EXTENDED

- Fire - Assessed for integrity only use on insulated timber doorsets for a duration up to 60 minutes, and uninsulated steel doorsets for a duration up to 240 minutes, in accordance with BS EN 1634.1. Report 190867 Issue 7 refers. (Z903.7N-SSS not included)
- Corrosion - Successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007. Report WIL 392103 refers. (Z903.7N-SSS not included)
- Accessibility - DDA compliant BS 8300 & Doc M.

Z903.4-SSS - 19MM DIAMETER UNSPRUNG

Grade 304 satin stainless steel.
19mm diameter lever on 53x4mm concealed fixing unsprung rose with stainless steel inner.
To suit doors 38-55mm thick.
Includes screw & bolt through fixings.
8mm spindle included.



Z903.7-SSS - 19MM DIAMETER SPRUNG

Grade 304 satin stainless steel.
19mm diameter lever on 53x7mm concealed fixing sprung rose with stainless steel inner.
To suit doors 38-55mm thick.
Includes screw & bolt through fixings.
8mm spindle included.



Z922.7-SSS - 22MM DIAMETER SPRUNG

Grade 304 satin stainless steel.
22mm diameter lever on 53x7mm concealed fixing sprung rose with stainless steel inner.
To suit doors 38-55mm thick.
Includes screw & bolt through fixings.
8mm spindle included.



Z903.7N-SSS - 19MM NARROW SPRUNG NEW

Grade 304 satin stainless steel.
19mm diameter lever on 30x64x8mm concealed fixing sprung rose with stainless steel inner.
To suit doors 38-55mm thick.
Includes screw & bolt through fixings.
8mm spindle included.



STAINLESS STEEL ESCUTCHEONS

<ul style="list-style-type: none"> ■ Fire - Assessed for integrity only use on insulated timber doorsets for a duration up to 60 minutes, and uninsulated steel doorsets for a duration up to 240 minutes, in accordance with BS EN 1634.1. Report 190867 Issue 7 refers (Z904.7N-SSS not included). ■ Corrosion - Successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007. Report WIL 392103 refers (Z904.7N-SSS not included). 	EURO	BLIND	OVAL	KEY	NARROW NEW	WASHROOM [▲]
4MM THICK concealed fixing escutcheons. 38mm centres. 53mm diameter. Grade 304 stainless steel inner with wood screws. Satin stainless steel.	Z904.4E-SSS	Z904.4B-SSS	Z904.4U-SSS	Z904.4L-SSS	-	Z904.4W-SSS
7MM THICK concealed fixing escutcheons. 38mm centres (Z904.7N - 43mm centres). 53mm diameter (Z904.7N - 30 x 64mm). Grade 304 stainless steel inner with wood screws. Satin stainless steel.	Z904.7E-SSS	Z904.7B-SSS	Z904.7U-SSS	Z904.7L-SSS	Z904.7N-SSS	Z904.7W-SSS

[▲] emergency release indicator included (see page 165)

ALUMINIUM ESCUTCHEONS

ESCUTCHEONS FOR EURO PROFILE CYLINDERS	
REF	DESCRIPTION
Z807.1/S	Satin anodised aluminium finish aluminium self-adhesive escutcheon
Z807.2/S	SAA finish aluminium screw fix escutcheon



STAINLESS STEEL CYLINDER SHROUD

External cylinder shroud for euro profile cylinder. 12.5mm high, supplied with common 8mm internal escutcheon, with fixings, satin stainless steel. Concealed fixing externally. Bolts pass through internal rose inner and lock at 38mm centres. Clip on cover internally conceals fixings.

Z904.SEC.SSS

