

# STAINLESS STEEL PULL HANDLES EXTENDED

These products have been successfully fire tested to BS EN 1634-1:2014 on steel doors up to 240 minutes integrity. Copy of WF Assessment Report No 387312 Issue 2 available upon request.

Pull handles have also been successfully tested to Grade 4 (240 hours neutral salt spray exposure) in accordance with BS EN 1670:2007 Building Hardware - Corrosion Resistance. Report No WIL 392103 refers.

Extra pairs of roses with stubby bolts in both 19mm and 22mm are also available separately.

## 225MM X 19MM DIAMETER GRADE 304 SSS PULL HANDLES

### Z905.1-SSS



Single pull handle.  
Satin stainless steel.  
19mm diameter.  
225mm centres.  
65mm projection.  
Bolt through fixing, to suit 44-54mm thick doors.

### Z905.1BB-SSS



Pair pull handles.  
Satin stainless steel.  
19mm diameter.  
225mm centres.  
65mm projection.  
Bolt through back to back fixing, to suit 44-54mm thick doors (or 12mm glass doors).

### Z905.1CF-SSS



Single pull handle.  
Satin stainless steel.  
19mm diameter.  
225mm centres.  
72mm projection.  
Surface fixing, with Z905.5.19 53 x 7mm concealed fix roses with stubby bolts.

### Z905.8F-SSS NEW



Fixed pull handle on plate set.  
Satin stainless steel.  
19mm diameter.  
225mm centres (pull handle).  
65mm projection.  
Surface fixing, with one 300x76x1.5mm plate with radius corners, plate drilled and csk four times.

### Z905.8-SSS



Pull handle and plate set.  
Satin stainless steel.  
19mm diameter.  
225mm centres (pull handle).  
65mm projection.  
Bolt through fixing, with one 300x76x1.5mm plate with radius corners drilled centrally for pull, plate drilled and csk four times.

### Z905.9-SSS



Pull handle and plates set.  
Satin stainless steel.  
19mm diameter.  
225mm centres (pull handle).  
65mm projection.  
Bolt through fixing, with two 300x76x1.5mm plates with radius corners, one drilled centrally for pull, both plates drilled and csk four times.

## 300MM X 19MM DIAMETER GRADE 304 SSS PULL HANDLES

### Z905.3-SSS



Single pull handle.  
Satin stainless steel.  
19mm diameter.  
300mm centres.  
65mm projection.  
Bolt through fixing, to suit 44-54mm thick doors.

### Z905.3BB-SSS



Pair pull handles.  
Satin stainless steel.  
19mm diameter.  
300mm centres.  
65mm projection.  
Bolt through back to back fixing, to suit 44-54mm thick doors (or 12mm glass doors).

### Z905.3CF-SSS



Single pull handle.  
Satin stainless steel.  
19mm diameter.  
300mm centres.  
72mm projection.  
Surface fixing, with Z905.5.19 53 x 7mm concealed fix roses with stubby bolts.

## 300MM X 22MM DIAMETER GRADE 304 SSS PULL HANDLES

### Z905.2-SSS



Single pull handle.  
Satin stainless steel.  
22mm diameter.  
225mm centres.  
65mm projection.  
Bolt through fixing, to suit 44-54mm thick doors.

### Z905.2BB-SSS



Pair pull handles.  
Satin stainless steel.  
22mm diameter.  
225mm centres.  
65mm projection.  
Bolt through back to back fixing, to suit 44-54mm thick doors (or 12mm glass doors).

### Z905.2CF-SSS



Single pull handle.  
Satin stainless steel.  
22mm diameter.  
225mm centres.  
72mm projection.  
Surface fixing, with Z905.5.22 53 x 7mm concealed fix roses with stubby bolts.