

NON-FIRE RATED GLAZING TAPES

When installing our LoPro or Slimport vision frames, glazing tape should be fitted on both sides of the glass or frames. The thickness of the tape will be determined by the thickness of the glass being used and the thickness of the door the frame is being fitted to. When applying the glazing tape, peel it off from the roll and place the exposed adhesive side directly on to the clean surface of the vision frame or glass to be glazed. Do not remove the liner until the glazing tape is in the proper position.

PVC FOAM TAPES WITH SINGLE SIDED SELF-ADHESIVE BACKING

Manufactured in the UK, these polyvinyl chloride foam tapes are supplied with single sided tape, based on an all weather solvent acrylic adhesive system. They are protected with an acrylic liner.

- Colour: Black.
- Sizes: Always 10mm wide. Available in five thicknesses, 1mm, 2mm, 3mm, 5mm and 8mm. Roll length varies depending on tape thickness.
- Tape: Single sided (suffix /SS).
- Temperature: Service temperature -20°C to +90°C. Application temperature +10°C to +45°C.
- Compression: Recommended compression 25%. Maximum compression 30%. Do not over compress.



REF	THICKNESS	WIDTH	COIL LENGTH	COLOUR
ZPGT-1010/SS	1mm	10mm	50 m	Black
ZPGT-2010/SS	2mm	10mm	40 m	Black
ZPGT-3010/SS	3mm	10mm	25 m	Black
ZPGT-5010/SS NEW	5mm	10mm	15 m	Black
ZPGT-8010/SS	8mm	10mm	10 m	Black

PVC FOAM TAPES WITH DOUBLE SIDED SELF-ADHESIVE BACKING

Also manufactured in the UK, these polyvinyl chloride foam tapes are supplied with double sided tape, based on an all weather solvent acrylic adhesive system. They are protected with an acrylic liner.

- Colour: Black.
- Sizes: 10mm or 20mm wide. Available in eight thicknesses, 1mm, 1.5mm, 2 mm, 3mm, 4mm, 5mm, 6mm and 8mm. Roll length varies depending on tape thickness.
- Tape: Double sided (suffix /DS).
- Temperature: Service temperature -20°C to +90°C. Application temperature +10°C to +45°C.
- Compression: Recommended compression 25%. Maximum compression 30%. Do not over compress.



REF	THICKNESS	WIDTH	COIL LENGTH	COLOUR
ZPGT-1010/DS	1mm	10mm	50 m	Black
ZPGT-1510/DS	1.5mm	10mm	46 m	Black
ZPGT-2010/DS	2mm	10mm	25 m	Black
ZPGT-3010/DS	3mm	10mm	20 m	Black
ZPGT-3020/DS	3mm	20mm	20 m	Black
ZPGT-4010/DS	4mm	10mm	20 m	Black
ZPGT-5010/DS	5mm	10mm	12 m	Black
ZPGT-6010/DS	6mm	10mm	10 m	Black
ZPGT-8010/DS	8mm	10mm	10 m	Black

ANEMOSTAT CLOSED CELL FOAM GLAZING TAPES

Manufactured in the USA, these Anemostat glazing tapes are closed cell polyvinyl chloride foam sealant with pressure sensitive adhesive on two sides, protected with a paper or polyethylene liner.

- Colour: Black.
- Sizes: Always 9.5mm wide. Available in four thicknesses, 1/32" (0.8mm), 1/16" (1.6mm), 1/8" (3.2mm), and 1/4" (6.4mm). Roll length varies depending on tape thickness.
- Tape: Double sided, with blue release paper.
- Temperature: Service temperature -20°C to +90°C. Application temperature +7°C to +45°C.



REF	THICKNESS	WIDTH	COIL LENGTH	COLOUR
GT-132*	0.8mm	9.5mm	200 feet (61 m)	Black
GT-116	1.6mm	9.5mm	200 feet (61 m)	Black
GT-18	3.2mm	9.5mm	100 feet (30 m)	Black
GT-14*	6.4mm	9.5mm	50 feet (15 m)	Black