



HUCK GUN

■ HUCK AIR GUN – 10224

Huck air gun for Huck bolts and Huck structural rivets diameters 4.8 & 6.4 mm (3/16' & 1/4')

The 10224 is the workhorse of Huck guns, a versatile all aluminium body that can install both Huck bolt's pin and collar and Huck structural blind rivets with the changeover of a nose assembly (priced separately). The HG-10224 is suitable for both truck fabrication workshops and smash repair operations. Built tough to stand up to the most rigorous working conditions.

SPECIFICATIONS

- **Weight**
2.8kg
- **Air Pressure**
6.21 – 6.9 bar (90-100psi)
- **Stroke**
21 mm
- **Pulling Force**
19kN @ 6.21 bar
- **Fastener Capacity***
Huck bolts & Huck rivets 4.8 & 6.4 mm (3/16' & 1/4') with different noses

*Nose additional cost



Free tool service, repairs & hire options when you purchase tools & fasteners from us**



■ LOCK BOLT & STRUCTURAL RIVET GUN – 10U05

Far® brand air gun for Huck bolts & Huck structural rivet diameters 4.8, 6.4 & 7.9 mm*

The 10U05 is a lightweight ergonomically balanced production tool designed for installation of Huck bolts and rivets. The tool accepts a wide range of nose assemblies which can be quickly and easily changed to suit Huck rivets and/or Huck bolts covering diameters sizes; 4.8 mm (3/16"), 6.4 mm (1/4"). *Plus 7.9mm diameter structural rivets, steel & aluminum only.

HG-10U05 Far® Gun Technical Data; Nose Assembly: supplied separately (additional cost), measurements excluding nose. HG-10U05 Pressure required: 6.21-6.9 bar or 90-100 psi. Stroke; 19.5 mm. Pulling force 22.7 kN. Far Gun HG-10U05 Accessories; Nose piece adapter, wrench, air fitting, oil bottle, mandrel deflector & manual.

** Free labour, parts & freight charges apply. Subject to minimum annual recurring spend with Aerobolt.