

S STEEL **A** ALUMINIUM **SS** STAINLESS



NUTSERT XTRALOK[®]

- Knurled body for better material grip
- Low profile thin wide flange
- Great resistance to vibration & spin-out



SMOOTH BODY RIVNUT

- Light weight, small diameter, thin wall
- Great for low torque applications
- Countersunk profile



HALF HEX NUTSERT

- Half hex & half round body
- Great resistance to unscrewing
- Chamfer provides easy insertion

S **A** **SS**

S **A** **SS**

S **SS**



PLUSNUT INSERT

- Heavy duty extended grip range
- Good for soft brittle materials
- Pre-bulb for easy installation



CLOSED END NUTSERT

- Dust & weather proof connection
- Closed end Hex inserts are also available
- Extended material grip range



FULL HEX NUTSERT

- Full hexagon shape body
- Excellent resistance to unscrewing
- Similar strength to weld & clinch nuts

S

S **SS**

S



WELL NUTS

- Can absorb shock, vibration & noise
- No special tools required
- Any material including glass



JACK NUTS

- Soft plastics or thin sheet steel
- Fast, inexpensive & easy to use
- Works well on uneven surfaces



THREADED STUDS

- Load bearing thread
- Strong re-usable bolt
- Good alternative to weld nuts

Neoprene Rubber

S

S