



Manufactured with synthetic and safe material that is similar to human hair.

MATERIAL SAFETY DATA SHEET PRIMER

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PRIMER

Company Name: Beauty Lash

SECTION 2 – COMPOSITION, INFORMATION ON INGREDIENTS

Component	CAS NO.	%by Weight(approximate)
H2O	7732-18-5	< 20
ethyl alcohol	64-17-5	>50
AA	108-24-7	<15
SILANE	1760-24-3	<15

SECTION 3 – HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW Appearance: colorless clear liquid. Flash Point: 16.6 deg C. Flammable liquid and vapor. May cause central nervous system depression. Causes severe eye irritation. Causes respiratory tract irritation. Causes moderate skin irritation. This substance has caused adverse reproductive and fetal effects in humans. Warning! May cause liver, kidney and heart damage. Target Organs: Kidneys, heart, central nervous system, liver.

Potential Health Effects Eye: Causes severe eye irritation. May cause painful sensitization to light. conjunctivitis and corneal May cause chemical damage. Skin: Causes moderate skin irritation. May cause cyanosis of the extremities.

Ingestion: May cause gastrointestinal irritation with nausea, vomiting and diarrhea. May cause systemic toxicity with acidosis. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness,

drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Inhalation: Inhalation of high concentrations may cause central nervous system effects characterized by nausea,

headache, dizziness, unconsciousness and coma. Causes respiratory tract irritation. May cause narcotic effects in high concentration. Vapors may cause dizziness or suffocation.

Chronic: May cause reproductive and fetal effects. Laboratory experiments have resulted in mutagenic effects. Animal studies have reported the development of tumors. Prolonged exposure may cause liver, kidney, and heart damage.

SECTION 4 – FIRST AID MEASURES

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Get medical aid. Gently lift eyelids and flush continuously with water. Skin: Get medical aid. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Flush skin with plenty of soap and water. Ingestion: Do NOT induce vomiting. If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid. Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid. Do NOT use mouth-to-mouth resuscitation. Notes to Physician: Treat symptomatically and supportively. Persons with skin or eye disorders or liver, kidney, chronic respiratory diseases, or central and peripheral nervous system diseases may be at increased risk from exposure to this substance. Antidote: Replace fluid and electrolytes.

SECTION 5 – FIRE FIGHTING MEASURE

General Information: Containers can build up pressure if exposed to heat and/or fire. As in any fire, wear a self-contained

breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a source of ignition and flash back. Will burn if involved in a fire.

Flammable Liquid. Can release vapors that form explosive mixtures at temperatures above the flashpoint. Use water spray to keep fire-exposed containers cool. Containers may explode in the heat of a fire. Extinguishing Media: For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. For large

fires, use water spray, fog, or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do NOT use straight streams of water. Flash Point: 16.6 deg C (61.88 deg F)

Autoignition Temperature: 363 deg C (685.40 deg F) Explosion Limits, Lower:3.3 vol % Upper: 19.0 vol % NFPA Rating: (estimated) Health: 2; Flammability: 3; Instability: 0 SECTION 6 – ACCIDENTAL RELEASE MEASURES

General Information: Use proper personal protective equipment as indicated in Section Spills/Leaks: Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. A vapor suppressing foam may be used to reduce vapors.

SECTION 7 – HANDLING AND STORAGE

Handling: Wash thoroughly after handling. Use only in a well-ventilated area. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing.

Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep container tightly closed. Avoid contact with heat, sparks and flame. Avoid ingestion and inhalation. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames Storage: Keep away from heat, sparks, and flame. Keep away from sources of ignition. Store in a tightly closed container. Keep from contact with oxidizing materials. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. Do not store near perchlorates,

peroxides, chromic acid or nitric acid.

SECTION 8 – EXPOSURE CONTROLS

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits.

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Ethyl alcohol	1000 ppm TWA	1000 ppm TWA; 1900 mg/m ³ TWA	1000 ppm TWA; 1900 mg/m ³ TWA
		3300 ppm IDLH	
Water	none listed	none listed	none listed

OSHA Vacated PELs: Ethyl alcohol: 1000 ppm TWA; 1900 mg/m³ TWA
Water: No OSHA Vacated PELs are listed for this chemical. Personal Protective Equipment

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure. Respirators: A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant a respirator's use. SECTION 9 – PHYSICAL / CHEMICAL PROPERTIES

Physical State: Clear liquid Appearance: colorless Odor: Mild, rather pleasant, like wine or whis pH: Not available. Vapor Pressure: 59.3 mm Hg @ 20 deg C Vapor Density: 1.59 Evaporation Rate: Not available. Viscosity: 1.200 cP @ 20 deg C Boiling Point: 78 deg

C Freezing/Melting Point:-114.1 deg C Decomposition Temperature:Not available. Solubility: Miscible. Specific Gravity/Density:0.790 @ 20°C Molecular Formula:C₂H₅OH Molecular Weight:46.0414

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures. Conditions to Avoid: Incompatible materials, ignition sources, excess heat, oxidizers. Incompatibilities with Other Materials: Strong oxidizing agents, acids, alkali metals, ammonia, hydrazine, peroxides, sodium, acid anhydrides, calcium hypochlorite, chromyl chloride, nitrosyl perchlorate, bromine pentafluoride, perchloric acid, silver nitrate, mercuric nitrate, potassium-tert-butoxide, magnesium perchlorate, acid chlorides, platinum, uranium hexafluoride, silver oxide, iodine heptafluoride, acetyl bromide, disulfuryl difluoride, tetrachlorosilane + water, acetyl chloride, permanganic acid, ruthenium (VIII) oxide, uranyl perchlorate, potassium dioxide. Hazardous Decomposition Products: Carbon monoxide, irritating and toxic fumes and gases, carbon dioxide. Hazardous Polymerization: Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

RTECS#:

CAS# 64-17-5: KQ6300000

CAS# 7732-18-5: ZC0110000

LD50/LC50:

CAS# 64-17-5:

Draize test, rabbit, eye: 500 mg Severe;

Draize test, rabbit, eye: 500 mg/24H Mild; Draize test, rabbit, skin: 20 mg/24H Moderate; Inhalation, mouse: LC50 = 39 gm/m³/4H;

Inhalation, rat: LC50 = 20000 ppm/10H;

Oral, mouse: LD50 = 3450 mg/kg;

Oral, rabbit: LD50 = 6300 mg/kg;

Oral, rat: LD50 = 9000 mg/kg;

Oral, rat: LD50 = 7060 mg/kg;

CAS# 7732-18-5:

Oral, rat: LD50 = >90 mL/kg; Carcinogenicity: CAS# 64-17-5: ACGIH: A4 - Not Classifiable as a Human Carcinogen CAS# 7732-18-5: Not listed by ACGIH, IARC, NIOSH, NTP, or

OSHA. Epidemiology: Ethanol has been shown to produce fetotoxicity in the embryo or fetus of laboratory animals. Prenatal exposure to ethanol is associated with a distinct pattern of congenital malformations that have collectively been termed the "fetal alcohol syndrome". Teratogenicity: Oral, Human - woman: TDLo = 41 gm/kg (female 41 week(s) after conception) Effects on Newborn - Apgar score (human only) and Effects on Newborn - other neonatal measures or effects and Effects on Newborn - drug dependence.

Reproductive Effects: Intrauterine, Human - woman: TDLo = 200 mg/kg (female 5 day(s) pre-mating) Fertility - female fertility index (e.g. # females pregnant per # sperm positive females; # females pregnant per # females mated). Neurotoxicity: No information available. Mutagenicity: DNA Inhibition: Human, Lymphocyte = 220 mmol/L.; Cytogenetic Analysis: Human, Lymphocyte = 1160 gm/L.; Cytogenetic Analysis: Human, Fibroblast = 12000 ppm.; Cytogenetic Analysis: Human, Leukocyte = 1 pph/72H (Continuous).; Sister Chromatid Exchange: Human, Lymphocyte = 500 ppm/72H (Continuous).

Other Studies: Standard Draize Test(Skin, rabbit) = 20 mg/24H (Moderate) Standard Draize Test: Administration into the eye (rabbit) = 500 mg (Severe).

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: Fish: Rainbow trout: LC50 = 12900-15300 mg/L; 96 Hr; Flow-through @ 24- 24.3°C Rainbow trout: LC50 = 11200 mg/L; 24 Hr; Fingerling (Unspecified) ria: Phytobacterium phosphoreum: EC50 = 34900 mg/L; 5-30 min;

Microtox test When spilled on land it is apt to volatilize, biodegrade, and leach into the ground water, but no data on the rates of these processes could be found. Its fate in ground water is unknown. When released into water it will volatilize

and probably biodegrade. It would not be expected to adsorb to sediment or bioconcentrate in fish. Environmental: When released to the atmosphere it will photodegrade in hours (polluted urban atmosphere) to an

estimated range of 4 to 6 days in less polluted areas. Rainout should be significant. Physical: No information available. Other: No information available.

SECTION 13 – DISPOSAL CONSIDERATIONS

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must

consult state and local hazardous waste regulations to ensure complete and accurate classification. RCRA P-Series: None listed. RCRA U-Series: None listed.

SECTION 14 – TRANSPORT INFORMATION

	US DOT	IATA	RID/ADR	IMO	Canada	TDG	
Shipping Name	ETHANOL					No information available.	
Hazard Class	3						
UN Number	UN1170						
Packing Group	II						

SECTION 15 – REGULATORY INFORMATION

US FEDERAL TSCA CAS# 64-17-5 is listed on the TSCA inventory. CAS# 7732-18-5 is listed on the TSCA inventory. Health & Safety Reporting List None of the chemicals are on the Health & Safety Reporting List. Chemical Test Rules None of the chemicals in this product are under a Chemical Test Rule. Section 12b None of the chemicals are listed under TSCA Section 12b. TSCA Significant New Use Rule None of the chemicals in this material have a SNUR under

TSCA.

SARA CERCLA Hazardous Substances and corresponding RQs None of the chemicals in this material have an RQ. SARA Section 302 Extremely Hazardous Substances None of the chemicals in this product have a TPQ. SARA Codes CAS # 64-17-5: acute, chronic, flammable. Section 313 No chemicals are reportable under Section 313. Clean Air Act: This material does not contain any hazardous air pollutants. This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors. Clean Water Act: Clean Water Act: None of the chemicals in this product are listed as Hazardous Substances under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. OSHA: None of the chemicals in this product are considered highly hazardous by OSHA. STATE CAS# 64-17-5 can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts. CAS# 7732-18-5 is not present on state lists from CA, PA, MN, MA, FL, or NJ. WARNING: This product contains Ethyl alcohol, a chemical known to the state of California to cause birth defects or other reproductive harm. California No Significant Risk Level: None of the chemicals in this product are listed. European/International Regulations European Labeling in Accordance with EC Directives Hazard Symbols: F Risk Phrases: R 11 Highly flammable. Safety Phrases: S 16 Keep away from sources of ignition - No smoking. S 33 Take precautionary measures against static discharges.

S 7 Keep container tightly closed. S 9 Keep container in a well-ventilated place. WGK (Water Danger/Protection) CAS# 64-17-5: 0 CAS# 7732-18-5: No information available. Canada - DSL/NDL CAS# 64-17-5 is listed on Canada's DSL List. CAS# 7732-18-5 is listed on Canada's DSL List. Canada - WHMIS This product has a WHMIS classification of B2, D2A, D2B. Canadian Ingredient Disclosure List CAS# 64-17-5 is listed on the Canadian Ingredient Disclosure List. Exposure Limits CAS# 64-17-5: OEL-AUSTRALIA:TWA 1000 ppm (1900 mg/m³) OEL-BELGIUM:T WA 1000 ppm (1880 mg/m³) OEL-CZECHOSLOVAKIA:TWA 1000 mg/m³;STEL 5000 mg/m³ OEL-DENMARK:TWA 1000 ppm (1900

mg/m³) OEL-FINLAND:TWA 1000 ppm (1900 mg/m³);STEL 1250 ppm (2400 mg/m³) OEL-FRANCE:TWA 1000 ppm (1900 mg/m³);STEL 5000 pp OEL-GERMANY:TWA 1000 ppm (1900 mg/m³) OEL-HUNGARY:TWA 1000 mg/m³;STEL 3000 mg/m³ OEL-THE NETHERLANDS:TWA 1000 ppm (1900 mg/m³) OEL-THE PHILIPPINES:TWA 1000 ppm (1900 mg/m³) OEL-POLAND :TWA 1000 mg/m³ OEL-RUSSIA:STEL 1000 mg/m³ OEL-SWEDEN:TWA 1000 ppm (1900 mg/m³) OEL-SWITZERLAND:TWA 1000 ppm (1900 mg/m³) OEL-THAILAND:TWA 1000 ppm (1900 mg/m³) OEL-TURKEY:TWA 1000 ppm (1900 mg/m³) OEL-UNITED KINGDOM:TWA 1000 ppm (1900 mg/m³) JAN9 OEL IN BULGARIA, COLOMBIA , JORDAN, KOREA check ACGIH TLV OEL IN NEW ZEALAND, SINGAPORE, VIETNAM check ACGI TLV

SECTION 16 – OTHER INFORMATION

US FEDERAL TSCA CAS# 64-17-5 is listed on the TSCA inventory. CAS# 7732-18-5 is listed on the TSCA inventory. Health & Safety Reporting List None of the chemicals are on the Health & Safety Reporting List. Chemical Test Rules None of the chemicals in this product are under a Chemical Test Rule. Section 12b None of the chemicals are listed under TSCA Section 12b. TSCA Significant New Use Rule None of the chemicals in this material have a SNUR under TSCA. SARA CERCLA Hazardous Substances and corresponding RQs None of the chemicals in this material have an RQ. SARA Section 302 Extremely Hazardous Substances None of the chemicals in this product have a TPQ. SARA Codes CAS # 64-17-5: acute, chronic, flammable. Section 313 No chemicals are reportable under Section 313. Clean Air Act: This material does not contain any hazardous air pollutants. This material does not contain any Class 1 Ozone depleters. This material does not contain any Class 2 Ozone depleters. Clean Water Act: Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. OSHA: None of the chemicals in this product are considered highly hazardous by OSHA STATE CAS# 64-17-5 can be found on the following state right to know lists: California, New Jersey, Pennsylvania, Minnesota, Massachusetts. CAS# 7732-

18-5 is not present on state lists from CA, PA, MN, MA, FL, or NJ. WARNING: This product contains Ethyl alcohol, a chemical known to the state of California to cause birth defects or other reproductive harm. California No Significant Risk Level: None of the chemicals in this product are listed. European/International Regulations European Labeling in Accordance with EC Directives Hazard Symbols: F Risk Phrases: R 11 Highly flammable. Safety Phrases: S 16 Keep away from sources of ignition - No smoking. S 33 Take precautionary measures against static discharges. S 7 Keep container tightly closed. S 9 Keep container in a well-ventilated place. WGK (Water Danger/Protection) CAS# 64-17-5: 0 CAS# 7732-18-5: No information available. Canada - DSL/NDSL CAS# 64-17-5 is listed on Canada's DSL List. CAS# 7732-18-5 is listed on Canada's DSL List. Canada - WHMIS This product has a WHMIS classification of B2, D2A, D2B. Canadian Ingredient Disclosure List CAS# 64-17-5 is listed on the Canadian Ingredient Disclosure List. Exposure Limits CAS# 64-17-5: OEL-AUSTRALIA:TWA 1000 ppm (1900 mg/m³) OEL-BELGIUM:T WA 1000 ppm (1880 mg/m³) OEL-CZECHOSLOVAKIA:TWA 1000 mg/m³;STEL 5000 mg/m³ OEL-DENMARK:TWA 1000 ppm (1900 mg/m³) OEL-FINLAND:TWA 1000 ppm (1900 mg/m³);STEL 1250 ppm (2400 mg/m³) OEL-FRANCE:TWA 1000 ppm (190 0 mg/m³);STEL 5000 pp OEL-GERMANY:TWA 1000 ppm (1900 mg/m³) OEL-HUNG ARY:TWA 1000 mg/m³;STEL 3000 mg/m³ OEL-THE NETHERLANDS:TWA 1000 ppm (1900 mg/m³) OEL-THE PHILIPPINES:TWA 1000 ppm (1900 mg/m³) OEL-POLAND :TWA 1000 mg/m³ OEL-RUSSIA:STEL 1000 mg/m³ OEL-SWEDEN:TWA 1000 ppm (1900 mg/m³) OEL-SWITZERLAND:TWA 1000 ppm (1900 mg/m³) OEL-THAILAND:T WA 1000 ppm (1900 mg/m³) OEL-TURKEY:TWA 1000 ppm (1900 mg/m³) OEL-UN ITED KINGDOM:TWA 1000 ppm (1900 mg/m³) JAN9 OEL IN BULGARIA, COLOMBIA , JORDAN, KOREA check ACGIH TLV OEL IN NEW ZEALAND, SINGAPORE, VIETNA M check ACGI TLV