

DNG-250

Let's Go Lower!

It's like the raging long river running through yet near and far....

Following the same nice features of DNG-200, Antari determines to compile and design the fogging machine and the condenser into one complete, solid yet still mobile compartment!

What are different of the new DNG-250 is that it has equipped with more efficient cooling system for the fogging, highly effective compressor which goes well with new style environmental friendly coolant and comes with new heater system to generate much lower fog outputs.

The new touch panel LCD monitor is designed ergonomically to make the display easily understood for operating.

Without the dry ice pitfalls yet with its similar effects, this DNG-250 can generate large volume dense beautiful fog nonstop till the very end...







Specification

Input voltage AC 220-240V, 50/60 Hz 3.8-6.5A

Refrigerant R-404A

 Start current
 240V / 36.1A

 Rated power
 240V / 1600W

Warm-up time 240V / 8 minutes (approx.)

Fluid consumption 100 ml / min (100% output)

Fluid tank capacity 10L (2.64 gal)

Compatible fluid Antari FLL Low Fog Liquid Ambient temp. range $0^{\circ}\text{C} \sim -20^{\circ}\text{C} (32^{\circ}\text{F} \sim -68^{\circ}\text{F})$

Output 120 m² / min

Control Volume and Timer Mode, DMX512

DMX channels 1 Channel

Optional accessoriesFDNG-250 Flight caseDimensionL 780 W 608 H 715 mmWeight130 KG (286.60 lbs.)

