## KONTROL16

# **KONTROL36**

# KONTROL192

Page A 1

Page B

DMX512 protocol with 16 channels

Independent control of 4 fixtures, 4ch each (RGBW or RGBA)

### Sound-activated

Preset	9 colour preset for an immediate operation
Macro	Virtual colour wheel to scroll the whole colour spectrum
Power	9~12V DC 500mA
DMX Interface	3-pin XLR
Dimensions	325 x 140 x 52mm
Weight	1.4kg



ス

C





 DMX512 protocol with 36 channels

 Independent control of 6 fixtures, 6ch each (RGBWAU)

 Sound-activated

 Preset
 18 colour preset for an immediate operation

 Macro
 Virtual colour wheel to scroll the whole colour spectrum

 Power
 9-12V DC 500mA

 DMX Interface
 3-pin XLR

 Dimensions
 393 x 140 x 50mm

 Weight
 1.5kg



50

www.event-lighting.com.au

### DMX512 protocol with 192 channels

### Independent control of 12 fixtures, 16ch each

### Sound-activated/3RU compatible

Scenes 240 programmable scenes (30 banks of 8 scenes)

Chases 6 chased of up to 240 scenes per chase

- **Power** 9~12V DC 500mA
- DMX Interface 3-pin XLR

MIDI Signal 5-pin din standard interface

Dimensions 482 x 132 x 73mm

Weight 2.6kg





# **KONTROL192**