



	Lux	@ 25°			
		2.0m	4.0m	6.0m	8.0m
		Ø 0.88	Ø 1.77	Ø 2.65	Ø 3.55
	R	3,950	470	159	68
ĺ	G	7,220	854	324	142
	В	10,550	1,405	487	205
	W	6,790	814	298	115
Ī	Full	22,500	3,040	950	402





Photometrics	
Light Source	9x 15 W RGBW 4-in-1 LEDs
Beam Angle	25°
Output	22,500 lux @ 2 m full on
PWM	20,000 Hz
LED Lifespan	50,000 hours
Effects	
Dimming	0~100%, 3 dimming curves
Strobe	0.5~20 Hz
Power	
Input Voltage	100~240 V AC, 50/60 Hz
Power Consumption	150 W
Connection	Seetronic® outdoor TRUE1 in/out
Control	
Operation Modes	DMX, manual, auto, sound active, master/slave
RDM	Change DMX Address
Control Protocol	DMX512, RDM, (optional: Wireless DMX)
DMX Channels	4/6/8
Control Interface	Seetronic® 3-pin outdoor DMX in/out
Display	Full colour LCD touch screen
Housing	
Housing Materials	Die-cast aluminium
Housing Finish	Matte black
Cooling	Fanless cooling with temperature protection
IP Rating	IP65
Net Weight	6.5 kg
Accessories	
Included	1x 1 m Seetronic® outdoor powerkon extension cable
	1x 1 m Seetronic® outdoor DMX extension cable
Optional	Road Case: PAR9CASE
	Barn Door: PAR9BD

## **PAR9X150**

9x 15 W OUTDOOR RGBW PARCAN

The PAR9X15O is a mid-sized outdoor rated fixture, featuring 9x 15 W RGBW LEDs in a diecast aluminium housing, a 25° beam angle and the ability to install wireless DMX.

