M1S100RGBW Spot Head





Why only have only 7 colours from 1 wheel or a selection of a few colours from 2 wheels when you can have full RGBW control? The 100W of RGBW LED complete with 8 bit dimming control per colour will provide a pallete with limitless options and unparalleled precision. Featuring an indexable, replaceable and rotating gobo wheel and a fixed gobo wheel, multiple prisms and frost, iris, electronically controlled focus and all standard features including battery powered menu, RDM, DMX upgradable, large flippable LCD and an automatic temperature controlled fan, this unit will ensure fantastic results every time!

Details

Input Voltages: 100V~240V AC, 50/60Hz

Power Consumption: 180W

Light source: advanced 100W RGBW LED module

Power Connection: Neutrik® Powercon input and output connection

LED life: 60,000 hours

Lux: 8500 lumen, 7780 lux RGBW full on @2.5M

Beam angle: 13° PWM: 1,200Hz Colors: full color

Gobos: 1pc 7 + open fixed gobo wheel, 1pc 7 + open interchangeable rotating gobo wheel (outside

Ø27mm, inside Ø22mm)

Effect: 3 facets, 8 facets prism, frost, fast speed iris

Dimmer: 0-100% dimmer

Strobe: 0.5 - 26 Hz

Focus: linearly focusing controlled by DMX

Head movement: Pan: 630°(4.0 sec)or 540°(3.58 sec), Tilt 265°(2.8 sec).16-bit resolution, auto

repositioning

Control: DMX512, 3-pin XLR interfaces, 26/33/17/18 channel mode

Other function: wireless DMX is available

2.4 inch colour LCD display with back-up power.

Thermostat Controlled, variable speed fan

RDM and software upgrade via DMX.

Net weight: 13Kg

Overall Size: 343x262x456mm


Rigging: 1pc omega brackets with 1/4 – turn guick locks

Road case available

M1S100RGBW Tech Specs



Photometric Data



Diameter (m)		Ø0.59	Ø1.14	Ø1.7	Ø2.25
LUX Intensity	R	1139	299	178	130
	G	3293	838	420	255
	В	470	118	107	83
	W	3446	875	441	275
	Full	7780	1971	941	568

Static & Rotating Gobos

Static gobos



Rotating gobos








370







Dimensional Diagrams



DMX Chart

(2)		
CH1	Pan	⑥ 0 → 630/540°
CH2	Tilt	© 0 — → 265°
СНЗ	Speed	0 Pan/Tilt → 255
CH4	Shutter Function	Normal Of Pulse Of Random
CH5	Shutter	Open Of Slow Off Fast
CH6	Dimmer	0 • 255
CH7	Color Function	© Slow Fa
CH8	Color 1	°C (3200k 4200k 5600k 8000k) 0 2st
СН9	Color 2	● ● ● ○ ● ● 5
CH10	Red	0->100%
CH11	Green	0->100%
CH12	Blue	0->100%
CH13	White	0->100%
CH14	Rot Gobo Function	(©), (©) (© (©)
CH15	Rotating Gobo	❷ ❸ ⊜ ❷ ⑤ ※ ◎
CH16	GoboRot Function	(© (© (©) (©, •
CH17	Gobo Rot	○ 0 → 250 ○
CH18	Gobo Funcation	● ③ ③ ③ 》
CH19	Static Gobo	
CH20	Prism	○
CH21	Prism Rot	0 → 127 (128 → 255
CH22	Focus Function	0 255 (5、7.5、10、15、20) m
CH23	Focus	
CH24	Iris Function	0 ○ → ○ 255
CH25	Iris	$0 \bigcirc \longrightarrow \bigcirc \longrightarrow \bigcirc 255$
CH26	Control	(Pan&Tit、Color、Gobo、Other) Reset All Display off/on Hibernation