





CERAMIC TOILET SUITE



Ceramic wall faced toilet suite Clean Flush, Nanoglaze, Easy Care Height

- Stylish minimalist design, sits flat against wall
- Clean Flush rimless pan design for an efficient, powerful flush Easy care height, pan height 440 mm
- Compliant with AS1428.1 Ambulant guidelines
- White vitreous china with nanoglaze surface, easy to clean
- Soft-closing, easy-clean quick release seat with stainless steel pins
- S or P trap
- Universal cistern, suits back entry or bottom entry plumbing

ORDER CODE	191760 191758 191843 191756	Modia WF, Deluxe seat Modia WF, Slim seat Modia WF, Flat seat Modia WF, Classic seat	Old code: STO-305-05 Old code: STO-305-03 Old code: n/a Old code: STO-305-01
CISTERN	Universal, suits back entry inlet or bottom entry plumbing. Left and right bottom entry inlet points.		
PAN	Wall faced close coupled with rimless pan design.		
TRAPS	Universal trap, suitable for S or P trap installations.		
SEAT	Quick release seat with stainless steel hinges, soft closing.		

4 star rating 4.5/3 litre water saving flush. WELS

SETOUT Variable 90-180 using supplied connector; 150mm recommended. This is a close coupled toilet suite — the cistern is fixed directly to the FIXING

pan and does not require wall fixing.

Pan may be bedded with cement base or using silicone sealant.

OPTIONS SEAT TOILET



DELUXE SEAT (40mm lid)

- Premium quality
- Easy to clean, anti-scratch
- Rigid, ceramic-like surface
- Made from Thermoset (UF)

SLIM SEAT (20mm lid)


- Premium quality
- Easy to clean, anti-scratch
- Rigid, ceramic-like surface
- Made from Thermoset (UF)


FLAT SEAT


- Premium quality
- Easy to clean, anti-scratch
- Rigid, ceramic-like surface - Made from Thermoset (UF)

CLASSIC SEAT (40mm lid)

- Lightweight, shiny finish
- Easy to clean
- Rigid, ceramic-like surface
- Made from Thermoplastic (PP)











🌎 Rimless Clean Flush pan – for an efficient, powerful flush. 🔷 Nanoglaze surface – ultra-smooth, anti-bacterial, easy to clean. 🛕 Easy care height – making it easier to get on and off the seat.





bathroom | kitchen | laundry

Please note

- Installation shall be in accordance with AS/NZS3500.
- All measurements are in millimetres. Height dimensions are to base of pan. Make allowance for bedding.
- Bedding: Pan may be bedded with cement base or using silicone sealant.
- Fix pan to floor using a sand cement mixture of 3:1 to a depth of 60mm. Do not use lime or fast-drying cement.
- Bracket fixing: The pan should be bedded with silicone sealant and fixed with the brackets supplied. Do NOT use epoxy type adhesives.
- Dimensions are nominal and subject to normal ceramic manufacturing variations.
- Specifications may vary without notice as part of our continuous improvement practices.
- Clean with a damp cloth. Do not use abrasive cleaners, liquids or pastes.