

APPLICATIONS:

The Unisonics FXP range is a single chamber device used to clean instruments and other hardware with ultrasonic energy in a mixed water/chemical solution.

SPECIFICATIONS:

Model	FXP4
Timer	LED ON/OFF Switch
Heating Power	Nil
Tank Material	Pressed 304 Stainless Steel
Tank Capacity	1.1L
Transducer Frequency	40kHz
Ultrasonic Power	50W
Overall Dimensions	175 x 165 x 180mm
Internal Tank	150 x 140 x 65mm
Gross Weight	2kg
Rack	Standard: 120 x 100 x 40mm Glass Platform Option: Basket with 5mm Mesh Aperture
Lid	Standard: Clear Plastic Included Option: PVC or Stainless Steel
Valve	Standard: No

CONSTRUCTION:

Certified by the Australian Made Campaign as Made and Owned in Australia.

Power is supplied by one single phase 10A plug.

Operating temperature should not exceed 60°C to maintain reliability and efficiency.

Minimum operating depth should not be less than 50mm.

Care should always be taken to avoid excessive spillage of solution when draining fluid.

Resin coated transducers and circuit board for moisture protection.

APPROVALS:

AS/NZS 3760:2010

AS/NZS 3100:2017

Certificate of Conformity No:E990002-(C-Tick)

Certificate for inclusion of medical device – Class 1 (T.G.A.)