


## Dolomite (Slab)

**Technical Specifications:** Walls Only, Light Commercial, Residential



Product Code: 48106.DOL.LP Color: Multi-Color

Material: Color Body Porcelain

Reference Icon	Description		Reference Icon	Description	
\$	Price Per Sq. Ft.	\$ 20.95 sq. ft.	15/64" 6 mm Thickness	Thickness	6 mm 15 "/ 64"
\$	Price Per m <sup>2</sup>	\$225.53 m <sup>2</sup>	Frost Resistant	Frost Resistant	Yes
\$	Price Per Piece	\$740.16 per slab	PET (Abranion Resistance) Does Not Apolly (Walls Only)	Abrasion Resistance (PEI Rating)	Not Applicable
- Lappato Polished	Finish	Lappato Polished	MOHS (Maroness Scale) Does Not Apply (Walls Cinly)	Abrasion Resistance (MOHS)	Not Applicable
Rectified Edge	Edge	Rectified	wet surfaces (COI) Does Not Apply (Walls Only)	Wet Surfaces (COF)	Not Applicable
Slipping Does Not Apply (Wall: Cinly)	Slip Rating	Not Applicable	Dynamic Coefficient of Friction Traction on Wet Surfaces Doce Not Apply (Walls Only)	Wet Surfaces (DCOF)	Not Applicable
V2 Shade Variation	Variation (V Rating)	V2			

Prices are subject to change. Please contact your Unique Versatile Ltd. sales representative to verify pricing. All sizing is nominal. Shading and variation is inherent in ceramics and natural stone. Please inspect before installing, no claims accepted after installation. If, for any reason, our products are regarded as unsatisfactory, we must be notified before installation, and consequently we will not make any allowances for labour costs for replacing material, or for other charges.



## Dolomite (Slab)

## ISO Standards



Below is a brief summary of the ISO Standard certifications. <u>Contact us</u> for the complete ISO technical data sheet sheets.

ISO Classification #	Certification	ISO Classification #	Certification
ISO 13006 (Classification)	Yes	ISO 10545-9 (Thermal Shock Resistance)	Yes
ISO 10545-2 (Dimensions and Surface Quality)	Yes	ISO 10545-10 (Moisture Expansion)	Yes
ISO 10545-3 (Water Absorption)	Yes	ISO 10545-11 (Crazing Resistance)	Yes
ISO 10545-4 (Rupture/Breaking Strength)	Yes	ISO 10545-12 (Frost Resistance)	Yes
ISO 10545-5 (Impact Resistance)	Yes	ISO 10545-13 (Chemical Resistance)	Yes
ISO 10545-6 (Deep Abrasion Resistance)	No	ISO 10545-14 (Stain Resistance)	Yes
ISO 10545-7 (Surface Abrasion Resistance)	Yes	ISO 13501-1 (Fire Resistance)	Yes
ISO 10545-8 (Linear Thermal Expansion)	Yes		

## **Packing Information**

Note: All Slabs are individually packaged. Dolomite Slab 48" x 106" / 120 cm x 270 cm weighs 102.63 lbs. /46.65 kilos.



