

# COAT

PRODUCT BROCHURE



For any questions about the contents of this brochure please get in touch with the COAT team; [hello@coatpaints.com](mailto:hello@coatpaints.com)

v1 08.04.2024



# CHOOSE YOUR PERFECT FINISH

Don't be fooled by 'jack of all trade' paints. All COAT finishes are formulated with their specific job in mind. Get a perfectly flawless finish that lasts - whatever the surface.

Do I need primer? We recommend primer for any new wood, MDF, UPVC, Vinyl or unstable looking surfaces. You'll also need to mist-coat brand new plaster before adding your COAT colour.

	Flat Matt Dead Matt 2%	Flat Matt Claypaint Dead Matt 2%	Soft Sheen Matt-ish 15%	Eggshell Matt 10%	Floor Paint Matt-ish 15%
<b>Normal Walls</b> Regular use areas	✓	✓	✓	—	—
<b>Wet or Dirty Walls</b> Bathrooms or Pet Areas	—	—	✓	—	—
<b>Breathable Walls</b> Lime plaster, heritage homes	—	✓	—	—	—
<b>Ceilings</b> The bit up top	✓	✓	✓	—	—
<b>Wood</b> Kitchen Cabinets, Skirting	—	—	—	✓	✓
<b>Metal</b> Radiators	—	—	—	✓	✓
<b>UPVC</b> Kitchen Cabinets, Doors	—	—	—	✓	✓
<b>Floors</b> Wood or Vinyl	—	—	—	—	✓



# FLAT MATT

## PRODUCT OVERVIEW

A water based durable finish flat matt (2%) emulsion. Designed for interior use on plastered walls and ceilings, prepared wood and primed metal. The water based formulation gives a durable, wipe-clean finish with extraordinary depth of colour. Low in odour, low VOC and quick to dry. It achieves the highest possible A+ rating for indoor air quality.

Sheen Level: 2 %  
VOC: Max 2.9g/L  
VOC Rating: A+

Average coverage:  
1 Litre Tin 10m<sup>2</sup>  
2.5 Litre Tin 25m<sup>2</sup>  
5 Litre Tin 50m<sup>2</sup>  
2\* coats recommended  
Touch dry in 2hr, Re-coat in 4hr.

Produced in accordance with ISO 14000  
series of environmental management standards

High Opacity  
Fast Drying  
Water Based  
Low Odour  
Washable  
Scrub Class 1 rated to ISO 11998  
Pet Safe/Child Safe EN71-3

Available in 1L, 2.5L, 5L

Application: Brush, Roller, Spray.



# TECHNICAL DATA SHEET

# COAT

**PRODUCT**

COAT Durable Matt Interior Emulsion

**CODE**

Date:

22nd September 2022

**VERSION**

3.0

Issued By:

R Green

**DESCRIPTION**

A water based durable finish flat matt (2%) emulsion, designed for interior use on plaster walls and ceilings, prepared wood and primed metal. The low VOC water based formulation gives a durable, wipe-clean finish with extraordinary depth of colour.

Available in 1L, 2.5L and 5L cans.

**USE**

Stir thoroughly before use. Apply 2 coats of COAT paint by brush or roller application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.
- Bare metal requires a suitable primer.
- COAT paints are self-priming, however if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.
- For interior use, prime new, bare and porous surfaces using one coat of the appropriate COAT paint, thinned with water (1 part water, 9 parts paint).

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 30 minutes, recoatable after 2 hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

**CLEAN UP**

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings. Check for local paint recycling schemes.

## STORAGE & STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents/container to waste disposal site in accordance with local/national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. To avoid the risk of spillage, always store and transport in a secure, upright position. Safety data sheet available on request. Special precautions should be taken during surface preparation of pre-1960's paint surfaces as they may contain harmful lead. For further advice please contact us.

## VOCs

EU limit value for this product (Cat A/a): 30g/L (2010). This product contains max 2.9g/L VOC. French VOC Regulation A+ Rated

## OTHER INFORMATION

Scrub Class 1 rated to ISO 11998

Toy Safety Standard Pass BS EN 71-3: 2019+A1:2021, EN 71-3: 2019+A1:2021

For further advice or information regarding this product please contact us directly or visit [coatpaints.com](http://coatpaints.com).

The above information is to the best of our knowledge correct but does not constitute a Sales specification.

# FLAT MATT CLAYPAINT PRODUCT OVERVIEW

A water based breathable clay paint with a flat matt (2%) finish. Designed for interior use on lime plaster or similar traditional breathable materials across walls and ceilings. The ultra low VOC formulation gives a deep chalky finish with a breathable SD Value of 0.02. Low in odour and quick to dry, it achieves the highest possible A+ rating for indoor air quality.

Sheen Level: 2 %  
VOC: Max 2.9g/L  
VOC Rating: A+  
SD Value 0.02

Average coverage:  
2.5 Litre Tin 25m<sup>2</sup>  
5 Litre Tin 50m<sup>2</sup>  
2\* coats recommended  
Touch dry in 2hr, Re-coat in 4hr.

Produced in accordance with ISO 14000  
series of environmental management standards

High Opacity  
Fast Drying  
Water Based  
Low Odour  
Wipeable  
Scrub Class 2 rated to ISO 11998  
Pet Safe/Child Safe EN71-3

Available in 2.5L, 5L

Application: Brush, Roller.



# TECHNICAL DATA SHEET

# COAT

## PRODUCT

COAT Claypaint

## CODE

Date:

8<sup>th</sup> April 2024

## VERSION

1.0

Issued By:

R Green

## DESCRIPTION

A water based, flat matt (2%) clay paint emulsion, designed for interior use on plaster walls and ceilings. Particularly suitable for lime plastered walls. The ultra-low VOC and highly breathable water based formulation gives a chalky finish with extraordinary depth of colour.

Available in 2.5L and 5L cans.

## USE

Stir thoroughly before use, the high solids nature of this paint requires vigorous stirring. We recommend mechanical stirring where possible. Apply 2 coats of COAT paint by brush or roller application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time. For best results, try to keep a wet edge and complete one wall at a time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.
- COAT paints are self-priming, however if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.
- For interior use, prime new, bare and porous surfaces using one coat of the appropriate COAT paint, thinned with water (1 part water, 9 parts paint).
- Clay or lime plaster must be moistened prior to painting.

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 2 hours, re-coatable after 4 hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

## CLEAN UP

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings. Check for local paint recycling schemes.

## STORAGE & STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents/container to waste disposal site in accordance with local/national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. To avoid the risk of spillage, always store and transport in a secure, upright position. Safety data sheet available on request. Special precautions should be taken during surface preparation of pre-1960's paint surfaces as they may contain harmful lead. For further advice please contact us.

## VOCs

EU limit value for this product (Cat A/a): 30g/L (2010). This product contains max 2.9g/L VOC.

## OTHER INFORMATION

Toy Safety Standard (BS EN 71-3: 2019+A1:2021, EN 71-3: 2019+A1:2021): Pass.

Water Vapour Permeability (BS EN ISO 7783): between 0.025 and 0.03 (shade dependent).

VOC: Trace (less than 0.1%).

For further advice or information regarding this product please contact us directly or visit [coatpaints.com](http://coatpaints.com).

The above information is to the best of our knowledge correct but does not constitute a Sales specification.



# SOFT SHEEN PRODUCT OVERVIEW

A water based, moisture resistant, soft sheen finish (15%) emulsion. Designed for interior use on plaster walls and ceilings. The low VOC water based formulation gives an ultra durable, scrubbable finish with excellent opacity. Particularly suitable for areas such as kitchens and bathrooms where high humidity is encountered and high traffic areas. Low in odour, low VOC and quick to dry. It achieves the highest possible A+ rating for indoor air quality.

Sheen Level: 15%  
VOC: Max 30.0g/L  
VOC Rating: A+

Average coverage:  
1 Litre Tin 10m<sup>2</sup>  
2.5 Litre Tin 25m<sup>2</sup>  
5 Litre Tin 50m<sup>2</sup>  
2\* coats recommended  
Touch dry in 2hr, Re-coat in 4hr.

Produced in accordance with ISO 14000  
series of environmental management standards

High Opacity  
Fast Drying  
Water Based  
Low Odour  
Moisture and mould resistant  
Scrubbable  
Scrub Class 1 rated to ISO 11998  
Pet Safe/Child Safe EN71-3

Available in 1L, 2.5L, 5L

Application: Brush, Roller, Spray.



# TECHNICAL DATA SHEET

# COAT

## PRODUCT

COAT Soft Sheen Emulsion

## CODE

Date:

10th October 2022

## VERSION

4.0

Issued By:

R Green

## DESCRIPTION

A water based, moisture resistant, soft sheen finish (AV 18% depending on colour) emulsion designed for interior use on plaster walls and ceilings. The low VOC water based formulation gives a durable, wipe-clean finish with excellent opacity. Particularly suitable for areas such as kitchens and bathrooms where high humidity is encountered.

Available in 1L, 2.5L and 5L cans.

## USE

Stir thoroughly before use. Apply 2 coats of COAT paint by brush or roller application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Surfaces affected by mould growth should be treated with a fungicidal wash and mould inhibitor and allow to dry thoroughly before painting.
- Wash down and remove old flaking or defective coating.
- A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.
- COAT paints are self-priming, however if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.
- For interior use, prime new, bare and porous surfaces using one coat of the appropriate COAT paint, thinned with water (1 part water, 9 parts paint).

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 2-3 hours, recoatable after 4 hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

## CLEAN UP

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings. Check for local paint recycling schemes.

### **STORAGE & STABILITY**

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

### **HEALTH, SAFETY & ENVIRONMENTAL INFORMATION**

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents/container to waste disposal site in accordance with local/national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. To avoid the risk of spillage, always store and transport in a secure, upright position. Safety data sheet available on request. Special precautions should be taken during surface preparation of pre-1960's paint surfaces as they may contain harmful lead. For further advice please contact us.

### **VOCs**

EU limit value for this product (Cat A/b): 100g/L (2010). This product contains max 30g/L VOC.  
French VOC Regulation A+ Rated

### **OTHER INFORMATION**

Scrub Class 1 rated to ISO 11998

Toy Safety Standard Pass BS EN 71-3: 2019+A1:2021, EN 71-3: 2019+A1:2021

For further advice or information regarding this product please contact COAT direct or go to the website.

The above information is to the best of our knowledge correct but does not constitute a Sales specification.

# INTERIOR EGGSHELL PRODUCT OVERVIEW

A water based eggshell finish (10%) emulsion, designed for interior use on prepared wood and primed metal. The ideal trim paint, levels to a smooth finish. The low VOC water based formulation gives a durable, scrubbable finish with extraordinary depth of colour. Low in odour, low-VOC and quick to dry, it achieves the highest possible A+ rating for indoor air quality.

Sheen Level: 10%  
VOC: Max 30.0g/L  
VOC Rating: A+

Average coverage:  
1 Litre Tin 10m<sup>2</sup>  
2.5 Litre Tin 25m<sup>2</sup>  
5 Litre Tin 50m<sup>2</sup>  
2\* coats recommended  
Touch dry in 2hr, Re-coat in 4hr

Produced in accordance with ISO 14000  
series of environmental management standards

High Opacity  
Fast Drying  
Water Based  
Low Odour  
Self-leveling  
Scrubbable  
Scrub Class 1 rated to ISO 11998  
Pet Safe/Child Safe EN71-3

Available in 1L, 2.5L, 5L

Application: Brush, Roller, Spray.



# TECHNICAL DATA SHEET

# COAT

**PRODUCT**

COAT Interior Eggshell Emulsion

**CODE**

Date:

22nd September 2022

**VERSION**

3.0

Issued By:

R Green

**DESCRIPTION**

A water based eggshell finish (10%) emulsion, designed for interior use on plaster walls and ceilings, prepared wood and primed metal. The low VOC water based formulation gives a durable, wipe-clean finish with extraordinary depth of colour.

Available in 1L and 2.5L cans.

**USE**

Stir thoroughly before use. Apply 2 coats of COAT paint by brush or roller or application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.
- Bare metal requires a suitable primer.
- COAT paints are self-priming, however if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.
- For interior use, prime new, bare and porous surfaces using one coat of the appropriate COAT paint, thinned with water (1 part water, 9 parts paint).

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 60 minutes, recoatable after 4 hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

**CLEAN UP**

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings. Check for local paint recycling schemes.

## STORAGE & STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents/container to waste disposal site in accordance with local/national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. To avoid the risk of spillage, always store and transport in a secure, upright position. Safety data sheet available on request. Special precautions should be taken during surface preparation of pre-1960's paint surfaces as they may contain harmful lead. For further advice please contact us.

## VOCs

EU limit value for this product (Cat A/a): 30g/L (2010). This product contains max 30g/L VOC.  
French VOC Regulation A+ Rated

## OTHER INFORMATION

Scrub Class 1 rated to ISO 11998

Toy Safety Standard Pass BS EN 71-3: 2019+A1:2021, EN 71-3: 2019+A1:2021

For further advice or information regarding this product please contact COAT direct or go to the website.

The above information is to the best of our knowledge correct but does not constitute a Sales specification.

# EXTERIOR EGGSHELL PRODUCT OVERVIEW

A water-based eggshell finish (20%) emulsion with superior weatherproof properties, designed for exterior use on prepared masonry, wood and primed metal. The low VOC water-based formulation gives a durable finish with extraordinary depth of colour. Low in odour, and quick to dry it achieves the highest possible A+ rating for air quality.

Sheen Level: 20%  
VOC: Max 30.0g/L  
VOC Rating: A+

Average coverage:  
1 Litre Tin 10m<sup>2</sup>  
2.5 Litre Tin 25m<sup>2</sup>  
5 Litre Tin 50m<sup>2</sup>  
2\* coats recommended  
Touch dry in 2hr, Re-coat in 4hr

Produced in accordance with ISO 14000  
series of environmental management standards

High Opacity  
Fast Drying  
Water Based  
Weather resistant  
Anti-colour fade  
Washable  
Scrub Class 1 rated to ISO 11998  
Pet Safe/Child Safe EN71-3

Available in 1L, 2.5L

Application: Brush, Roller, Spray.



**TECHNICAL  
DATA  
SHEET**

# COAT

**PRODUCT**

COAT Exterior Eggshell Emulsion

**CODE**

Date:

22nd September 2022

**VERSION**

3.0

Issued By:

R Green

**DESCRIPTION**

A water-based eggshell finish (20%) emulsion with superior weathering properties, designed for exterior use on prepared wood and primed metal. The low VOC water-based formulation gives a durable finish with extraordinary depth of colour.

Available in 1L cans and 2.5L cans.

**USE**

Stir thoroughly before use. Apply 2 coats of COAT paint by brush or roller or application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.
- Bare metal requires a suitable primer.
- Not suitable for exterior plastic surfaces or decking.

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 1 – 2 hours, recoatable after 4 hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).



## **CLEAN UP**

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings. Check for local paint recycling schemes.

## **STORAGE & STABILITY**

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

## **HEALTH, SAFETY & ENVIRONMENTAL INFORMATION**

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents/container to waste disposal site in accordance with local/national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. To avoid the risk of spillage, always store and transport in a secure, upright position. Safety data sheet available on request. Special precautions should be taken during surface preparation of pre-1960's paint surfaces as they may contain harmful lead. For further advice please contact us.

## **VOCs**

EU limit value for this product (Cat A/d): 130g/L (2010). This product contains max 30g/L VOC. French VOC Regulation A+ Rated

## **OTHER INFORMATION**

Scrub Class 1 rated to ISO 11998

Toy Safety Standard Pass BS EN 71-3: 2019+A1:2021, EN 71-3: 2019+A1:2021

For further advice or information regarding this product please contact COAT direct or go to the website.

The above information is to the best of our knowledge correct but does not constitute a Sales specification.

# FLOOR PAINT PRODUCT OVERVIEW

A water based eggshell (20%) finish. Designed for interior use on prepared wood floors, concrete and other general household flooring. The low VOC water based formulation gives a durable, scrubbable finish with good hardness and scuff resistance. Low in odour, low-VOC and quick to dry it achieves the highest possible A+ rating for indoor air quality.

Sheen Level: 20%  
VOC: Max 30.0g/L  
VOC Rating: A+

Average coverage:  
1 Litre Tin 10m<sup>2</sup>  
2.5 Litre Tin 25m<sup>2</sup>  
5 Litre Tin 50m<sup>2</sup>  
2\* coats recommended  
Touch dry in 2hr, Re-coat in 4hr

Produced in accordance with ISO 14000  
series of environmental management standards

High Opacity  
Fast Drying  
Water Based  
Low Odour  
Washable  
Scrub Class 1 rated to ISO 11998  
Pet Safe/Child Safe EN71-3

Available in 2.5L, 5L

Application: Brush, Roller.



# TECHNICAL DATA SHEET

# COAT

## PRODUCT

COAT Floor Paint, Interior Eggshell Emulsion

## CODE

Date:

1st March 2023

## VERSION

3.0

Issued By:

R Green

## DESCRIPTION

A water based eggshell finish (20%) one part acrylic floor paint. Designed for interior use on wood floors, concrete and other general household flooring. The low VOC water based formulation gives a durable, wipe-clean finish with good hardness and scuff resistance.

Available in 2.5L and 5L cans.

## USE

Stir thoroughly before use. Apply 2 coats of COAT paint by brush or roller or application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

- Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.
- Wash down and remove old flaking or defective coating.
- A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint. Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.
- COAT paints are self-priming, however if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.
- For interior use, prime new, bare and porous surfaces using one coat of the appropriate COAT paint, thinned with water (1 part water, 9 parts paint).
- Ensure new concrete is thoroughly dried and cured before painting on it. Algae, fungal or mould growth should be removed and treated with a fungicidal wash.

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 60 minutes, recoatable after 4 hours. Walk on after 24 hours. Allow longer in cool or damp conditions. (Do not apply at temperatures below 5°C).

## CLEAN UP

Remove as much product as possible from brushes and equipment before cleaning with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings. Check for local paint recycling schemes.

## STORAGE & STABILITY

Store upright in dry conditions above 5°C. Protect from frost. To avoid risk of spillage, always store and transport in a secure upright position.

## HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

Contains a reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), 2-methyl-2H-isothiazol-3-one and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. If medical advice is needed, have product container or label to hand. Keep out of reach of children. Dispose of contents/container to waste disposal site in accordance with local/national regulations. Ensure good ventilation during application and drying. Do not get in eyes, on skin or on clothing. IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. IF ON SKIN: Wash immediately with soap and water or a proprietary skin cleaner. Do not use solvent or thinners. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. To avoid the risk of spillage, always store and transport in a secure, upright position. Safety data sheet available on request. Special precautions should be taken during surface preparation of pre-1960's paint surfaces as they may contain harmful lead. For further advice please contact us.

## VOCs

EU limit value for this product (Cat A/a): 30g/L (2010). This product contains max 10g/L VOC.  
French VOC Regulation A+ Rated

## OTHER INFORMATION

Scrub Class 1 rated to ISO 11998

Toy Safety Standard Pass BS EN 71-3: 2019+A1:2021, EN 71-3: 2019+A1:2021

For further advice or information regarding this product please contact COAT direct or go to the website.

The above information is to the best of our knowledge correct but does not constitute a Sales specification.



# APPLICATION AND STORAGE

Stir thoroughly before use. Apply 2 coats of COAT paint by brush or roller application. If light or bright colours are to be used an additional coat may be required. Tones of separate batches may vary slightly, for colour consistency purchase sufficient paint for the complete job at one time.

Preparation of the surface to be painted is vital to the performance of your COAT paint.

Make good any structural cracks or defects and match the finish to the existing substrate. Use flexible fillers only.

Wash down and remove old flaking or defective coating.

A glossy painted surface must be sanded to a matt finish prior to applying the first coat of paint.

Avoid the inhalation of dust. Wear a suitable face mask when dry sanding.

Bare metal requires a suitable primer.

COAT paints are self-priming, however if a heavily repaired substrate has a wide variation of porosity and colours, priming is recommended as a first coat to create an even base colour.

For interior use, prime new, bare and porous surfaces using one coat of the appropriate COAT paint, thinned with water (1 part water, 9 parts paint). For lime plaster, wet the wall as well before applying our COAT Claypaint.

Coverage approximately 10m<sup>2</sup> per Litre. Touch dry in 2 hours, re-coatable after 4 hours. Allow longer in cool or damp conditions.

Do not apply at temperatures below 5oC. Store upright in dry conditions above 5oC. Protect your tins from frost.

To avoid risk of spillage, always store and transport in a secure upright position.

# SPRAYERS

When it comes to sprayers, we recommend using a good quality airless sprayer. This type of spray equipment gives less over-spray, and has the pressure to ensure good flow and finish with COAT paints.

We recommend thinning COAT paint by 10% when using airless spraying equipment, but please read the equipment manufacturers instructions. Thin paint using water only. This applies to our Flat Matt, Soft Sheen, Interior and Exterior Eggshell finishes only.

You should experiment with control and flow on an inconspicuous area first, until you are happy and comfortable to carry on. The amount of paint delivered by the airless is determined by the size of the tip used, and this will vary depending on the finish being sprayed. When airless spraying, start at a corner, work from the top down and keep your strokes steady and smooth as a lot of paint is going on to the surface in a short period of time. Two coats at a generous thickness with enough drying time between coats will give you the best performance and surface hardness.

Disclaimer: we're happy to give this guidance in good faith, but we can't offer any warranty as the skill of application and site conditions are beyond our control. We don't accept liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

Health & Safety advice: The pressure at the tip of the Air-less spray gun is normally in the 3000 psi (207 bar) range and can cause real injury. Keep hands and fingers away from the tip while pressure is on the machine. When spraying, wear a mask in a well ventilated area.

Always protect yourself with eye goggles with side protectors, gloves and overalls.



# COAT

PRODUCT BROCHURE

