

Dough Planetary Mixer/Kneader

(Taiwan Made)

Thermal overload protection.
 All metal and die-cast aluminum body.
 7-Foot power cord.
 Transmission is made of harden alloy steel gears.
 All shafts are mounted in ball bearings.
 3 mixing speeds
 Transmission type:BELT Driven
 Planetary-mixing action ensures perfect results. V-10
 Heat-treated steel alloy gear mechanism for durability.
 Safety Guard shut-off automatic when guard is opened at any speed.
 Simple hand lift for tool change and bowl removal.
 Accessory:1 PC S/S Bowl,1 PC Alum. Alloy Dough Hook,1 PC Alum. Alloy Flat Beater/Paddle,1 PC S/S Wire Whip



Item	Bowl Capacity	Dimension (in)	Flour Capacity	Dough Capacity	Agitator Speeds Capacity	Motor	Voltage Power	N.W./ G.W.
AV-01	10Qt	17x12x23	2.2 lb	3.5 lb	150/280/635 RPM	1/3 HP	110V/60Hz/1	84 lb/117 lb
AV-02	20 Qt	23x18.5x31	6.6 lb	11 lb	76 / 142 / 259 RPM	1/2 HP	110V/60Hz/1	199 lb/256 lb



Interlocking mechanism prevents mixing until guard is fully closed.
 3 mixing speeds,30 minutes Timer with auto shut-off. Shift speed must be stop the mixer first.
 Motor thermal overload protection.
 All metal and die-cast aluminum body.
 Transmission is made of harden alloy steel gears and mounted in ball bearings.
 Transmission type:GEAR Driven(HUB-30 & HUB-40 only)
 BELT Driven(V-60 & V-80 only)
 Precision-milled, heat-treated steel alloy gear for durability.
 Simple hand lift for tool change and bowl removal.
 High polish stainless steel meets food industry sanitation needs.

Accessory: 1 PC S/S Bowl
 1 PC Alum. Alloy Dough Hook
 1 PC Alum. Alloy Flat Beater/Paddle
 1 PC S/S Wire Whip
 1 x Universal #12 Hub attachment (HUB-30 & HUB-40&HUB-50 only)
 (for meat grinder/ vegetable slicer)
 1 x S/S Security Guard & 1 x Bowl Dolly (V-80 only)



Item	Bowl Capacity	Dimension (in)	Flour Capacity	Dough Capacity	Agitator Speeds	Hub Speeds	Motor Power	Voltage	Net Weight	Gross Weight
HUB-30	30 Qt	26x22x47	13.2 lb	22 lb	78/140/250 RPM	136/245/437 RPM	1 HP	110V/60Hz/1	352 lb	427 lb
HUB-40	40 Qt	27x23x50	22 lb	35 lb	50/105/230 RPM	96/183/402 RPM	1.5 HP	220V/60Hz/1	419 lb	562 lb
HUB-50	50 Qt	27x23x50	26.5 lb	44 lb	50/105/230 RPM	96/183/402 RPM	2 HP	220V/60Hz/1	441 lb	584 lb
V-60	60 Qt	35x22x56	48.5 lb	80 lb	104/197/331 RPM	119/226/380 RPM	3 HP	208V/60Hz/3	814 lb	940 lb
V-80	80 Qt	29x38x59	73 lb	121 lb	104/197/331 RPM	119/226/380 RPM	4 HP	208V/60Hz/3	882 lb	1005 lb

