

3 Electric Countertop Convection Oven



Features

- Can be used as a proofer and heated holding cabinet for added versatility
- Strong and light weight aluminum body
- Fully insulated door and body for up to 30% energy savings
- Double layer door and cabinet
- Full length door handle for easier door opening
- Easy LED temperature readout
- Clear poly-carbonate panel door for easy viewing
- Air baffle design for even heating throughout the cabinet
- Easily removable control board for easy cleaning and maintenance
- Field reverse-able door
- Removable corner bumpers to protect cabinet
- Warming setting allows temperatures to be manually adjusted up to 85° C (185° F) with knob thermostat
- Proofer setting allows temperatures to be manually adjusted down to 26.6° C (80° F); keep temperature below 46° C (115° F) to proof dough
- Humidity can be manually adjusted between 35% and 95% with knob adjuster



FD-21



FD-66G



FD-100

Specifications

MODEL	Dimensions W XDX H (In)	Number of Sheet Pan	Sheet Pan Size	Capacity(L)	V/Hz/Ph	Power	NET WEIGHT LB
FD-21	18.5 x 20x15	3	10X13	22	120V/60Hz/1	1.44KW	32
FD-66G	22 7/8x22 5/8x19 7/8	4	18X13	66	208-240V/60Hz/1	2.8KW	52
FD-100	31 4/5 x28 7/10x 22 4/5	4	26X18	100	208-240V/60Hz/1	4.6KW	101



CONFORMS TO UL STD.197
CONFORMS TO NSF STD.4



Certified To ANSI/NSF 7 Standards

If the data and structure update, without notice, subject to material object.