## 31"Depth Grab and Go Display Case



## **Features**

- Digital controller
- Finned evaporator
- Thermostatic expansion valve
- Automatic defrost
- LED light for every shelf
- With glass door
- Adjustable shelves
- Easy to mount 4" casters (lockable in front) are standard with all units
- Material: External: Stainless Steel
- With price label setting
- Automatic drain water
- Side double tampered glass
- Temperature : 36 to 46°F / 2 to 8°C
- Electrical: 115/60/1 with NEMA 5-20R plug, 10ft cord



GNG-59G GNG-76G GNG-101G

## **Specifications**

specifications							5-20R
SHELF NO.	Ext. Dimensions W X D X H (In)	V/Hz/Ph	AMPS	HP	Storge Capcity Sq-ft	POWER	NEMA PLUG
4	59.1x31x78.7	115/60/1	6.7A		20.5	1300W	5-20R
4	76.2x31x78.7	115/60/1	7.2A		26.7	1380W	5-20R
4	100.8X31X78.7	115/60/1	8.4A		35.6	1470W	5-20R
	SHELF NO. 4 4	SHELF NO. Ext. Dimensions W X D X H (In)   4 59.1x31x78.7   4 76.2x31x78.7	SHELF NO. Ext. Dimensions W X D X H (In) V/Hz/Ph   4 59.1x31x78.7 115/60/1   4 76.2x31x78.7 115/60/1	SHELF NO. Ext. Dimensions W X D X H (In) V/Hz/Ph AMPS   4 59.1x31x78.7 115/60/1 6.7A   4 76.2x31x78.7 115/60/1 7.2A	SHELF NO. Ext. Dimensions W X D X H (In) V/Hz/Ph AMPS HP   4 59.1x31x78.7 115/60/1 6.7A 1   4 76.2x31x78.7 115/60/1 7.2A 1	SHELF NO. Ext. Dimensions W X D X H (In) V/Hz/Ph AMPS HP Storge Capcity Sq-ft   4 59.1x31x78.7 115/60/1 6.7A 20.5   4 76.2x31x78.7 115/60/1 7.2A 26.7	SHELF NO. Ext. Dimensions W X D X H (In) V/Hz/Ph AMPS HP Storge Capcity Sq-ft POWER   4 59.1x31x78.7 115/60/1 6.7A 20.5 1300W   4 76.2x31x78.7 115/60/1 7.2A 26.7 1380W





Certified To ANSI/NSF 7 Standards


ſear

If the data and structure update, without notice, subject to material object.

## **Dimensions in inches**



GNG-59G



GNG-76G



GNG-101G

