

- > Reliable and dependable gear drive design
- > Long life gear box
- > 3 Speeds
- > #12 Power Hub for attachments
- > Quiet operation
- > Heat-treated hardened alloy steel gears and shaft
- > Stainless steel bowl safety guard
- > Side mounted controls. Separate start and stop buttons
- > Highest quality aluminum alloy used for maximum standard of hygiene
- > Safety interlock switch prevents operation when either bowl is lowered or guard is opened
- > 6 Foot cord and plug

STANDARD ACCESSORIES:

- Stainless steel bowl
- > Stainless steel wire whip
- > Aluminum flat beater, aluminum dough hook



514-737-9701 ₩ 888-275-4538 TOLL 844-218-8477

5659 ROYALMOUNT AVE, MONTREAL, QC, CANADA H4P2P9 12000 BISCAYNE BLVD, SUITE #108, MIAMI, FL, USA 33181

PROJECT NAME:		
LOCATION:	ark.	12
ITEM:	QTY:	
MODEL:		9-



MODEL	PM-20	(II)
CAPACITY	20 qt.	Intertek
FLOUR CAPACITY	9 lbs (4 kg)	
MOTOR	1.0 hp	C
ELECTRICAL	120V/60/1	Intertek
TRANSMISSION	Gear Drive	
SHIP WEIGHT	280 lbs	NEMA-5-15P
FREIGHT CLASS	85	
DIMENSIONS (WxDxH)	22" x 21.9" x 31.3"	AQ

Warranty: Two years parts, one year labor exclusive of wear items

Specifications subject to change without notice "PRIMO" is a registered trademark of MVP Group Corp. Printed July 2017