Salad & Sandwich Prep Table - Mega Top Refrigerator

Features

- -CFC free refrigerant and foam insulation.
- -Equipped with an electronic thermostat and digital LED temperature display for precise control and convenient reading.
- -Features a self-closing swing door for added convenience.
- -The magnetic gasket can be replaced without the need for any tools.
- -External construction comprises stainless steel framework.
- -Internally constructed with 304 stainless steel.
- -Incorporates auto defrosting and auto evaporation mechanisms to prevent condensation.
- -The coated copper tube, boasting a sturdy 0.7mm thickness, ensures durability.
- -Crafted from a single bent tube, minimizing the risk of leaks with only two welding joints.
- -The condenser is efficiently positioned inside the condensation pan to facilitate the evaporation of excess water.
- -Dispose of daily waste effortlessly with the stainless steel baseplate that lifts easily.
- -Adjustable and heavy-duty epoxy-coated wire shelves for flexible storage options.
- -Includes 1/6 size polycarbonate GN pans and a plastic cutting board.
- -Comes with easy-to-mount 4" casters (front casters equipped with brakes), standard with all units.
- -Electrical specifications: 115/60/1 with a NEMA 5-15P plug and a 10ft cord.

Temperature

-Interior temperature range: 1°C to 4°C (33°F to 40°F)

Warranty

-3 years parts and labour5 years compressor warranty











CSSU-72M

Only two

Solderless Interface





Specifications

Model	Door		Size Ext. Dimensions ns W x D x H (in)	Int Dimensions W x D x H (in)	V/Hz/Ph	AMPS	S Power of	Storage Capacity(cu-f	NEMA)PLUG	Ship Weight	Ship D (lbs) W x D x	
CSSU-29N	1 1	12	29 x 36 1/2 x 35 5/8 (42 1/2)	25 1/8 x 27 5/8 x 24 3/8	115/60/1	3	250W/0.34H	IP 8.5	5-15	245	32 1/8 x 37 1/4 x	47 5/8
CSSU-36N	1 2	15	36 1/4 x 36 1/2 x 35 5/8 (42 1/2)	32 1/4 x 27 5/8 x 24 3/8	115/60/1	3	300W/0.40H	HP 11.5	5-15	291 3	39 1/2 x 37 1/4 x	47 5/8
CSSU-48N	1 2	18	48 1/4 x 36 1/2 x 35 5/8 (42 1/2)	42 7/8 x 27 5/8 x 24 3/8	115/60/1	4	380W/0.51H	IP 15	5-15	320	51 1/2 x 37 1/4 x	47 5/8
CSSU-60N	1 2	24	61 1/8 x 36 1/2 x 35 5/8 (42 1/2)	55 7/8 x 27 5/8 x 24 3/8	115/60/1	4.5	400W/0.54H	HP 20	5-15	389	64 1/2 x 37 1/4 x	47 5/8
CSSU-72N	1 3	30	71 3/4 x 36 1/2 x 35 5/8 (42 1/2)	66 3/8 x 27 5/8 x 24 3/8	115/60/1	4.5	400W/0.54	HP 23	5-15	451	75 x 37 1/5 x 4	47 5/8









If the data and structure update, without notice, subject to material object.









